



Linear Drive Accessories

ø 10-80 mm

End Cap Mountings



For Linear-drive
• Series OSP-P

On the end-face of each end cap there are four threaded holes for mounting the actuator.
The hole layout is square, so that the mounting can be fitted to the bottom, top or either side, regardless of the position chosen for the air connection.

Material:

- Series OSP-P10 – P32: Galvanized steel.
- Series OSP-P40 – P80: Anodized aluminum.

The mountings are supplied in pairs.



Dimension Table (mm)										
Series	E	ØU	AB	AC	AD	AE	AF	CL	DG	Order No. (* Type A1 Type C1)
OSP-P10	-	3.6	12	10	14	20.2	11	1.6	18.4	0240 -
OSP-P16	18	3.6	18	10	14	12.5	15	1.6	26	20408 -
OSP-P25	27	5.8	27	16	22	18	22	2.5	39	2010 -
OSP-P32	36	6.6	36	18	26	20	30	3	50	3010 -
OSP-P40	54	9	30	12.5	24	24	38	-	68	- 4010
OSP-P50	70	9	40	12.5	24	30	48	-	86	- 5010
OSP-P63	78	11	48	15	30	40	57	-	104	- 6010
OSP-P80	96	14	60	17.5	35	50	72	-	130	- 8010

(*= Pair)

