



Flexcoil®

Specifications

Temperature Range
-40°F to +125°F

Vacuum Rating
To 28" Hg.

Diameter Tolerances
±.005"

Hardness
95A

Working Pressure
3:1 Safety Factor

Working Length
80-90% of Material Length

Resin Compliance
95A: NSF61
Meets UL94HB

Variations

Flexcoil variations are easy. If you don't see the color or length that you want, just ask us. We can configure Flexcoil to perfectly match your requirements.

Available in:

- B Blue
- G Neon Green
- R Red
- Y Yellow
- T Transparent Blue

Rigid Fitting with Strain Relief

Swivel Fitting with Strain Relief

Flexcoil® Coiled Polyurethane with Reusable Strain Relief Fittings

Part Number, Fitting & Color Code	Fitting Options	Standard Colors	Material Length	Working Length	Retracted Length	OD	ID	Coil OD	Working Pressure	Weight
PU316-5	— (2) 1/4" Rigid		5'	4'	2"					.23 lbs.
PU316-10	A= (1) 1/4" Rigid &	B G R	10'	8'	6"					.34 lbs.
PU316-15	(1) 1/4" Swivel	Y T	15'	12.5'	10 1/4"	5/16"	3/16"	1 7/8"	160 PSI	.46 lbs.
PU316-20	B= (2) 1/4" Swivel		20'	17'	14 1/2"					.56 lbs.
PU316-25			25'	20'	18 1/2"					.68 lbs.
PU14-5	— (2) 1/4" Rigid		5'	4'	2 1/2"					.23 lbs.
PU14-10	A= (1) 1/4" Rigid	B G R	10'	8'	6"					.41 lbs.
PU14-15	(1) 1/4" Swivel	Y T	15'	12.5'	9 1/2"					.59 lbs.
PU14-20	B= (2) 1/4" Swivel		20'	17'	13"	3/8"	1/4"	2 1/2"	130 PSI	.74 lbs.
PU14-25	6= (2) 3/8" Rigid		25'	20'	16"					.88 lbs.
PU14-30			30'	25.5'	19"					1.05 lbs.
PU14-50			50'	42.5'	32 1/2"					1.50 lbs.
PU516-10	— (2) 3/8" Rigid		10'	8'	7 1/2"					.68 lbs.
PU516-15	A= (1) 3/8" Rigid	B G R	15'	12.5'	11 1/2"					.89 lbs.
PU516-20	(1) 3/8" Swivel	Y T	20'	17'	15"	15/32"	5/16"	2 15/16"	130 PSI	1.11 lbs.
PU516-25	B= (2) 3/8" Swivel		25'	20'	19"					1.32 lbs.
PU516-30			30'	25.5'	23"					1.52 lbs.
PU38-10	4= (2) 1/4" Rigid		10'	8'	5 1/2"					1.00 lbs.
PU38-15	— (2) 3/8" Rigid		15'	12.5'	8 1/2"					1.40 lbs.
PU38-20	A= (1) 3/8" Rigid	B G R	20'	17'	11"					1.85 lbs.
PU38-25	(1) 3/8" Swivel	Y T	25'	20'	14"	9/16"	3/8"	4 1/8"	135 PSI	2.25 lbs.
PU38-30	B= (2) 3/8" Swivel		30'	25.5'	17"					2.63 lbs.
PU38-50			50'	42.5'	27 1/2"					3.23 lbs.

Variations Available:

Colors • Printing • Packaging

* In addition to color choice, select fittings for both ends of the coil.

30

People.Passion.Possibilities

www.freelin-wade.com

www.comoso.com

See page 34 for Fre-Thane® coils without fittings.

Available in:

- B Blue
- G Neon Green
- R Red
- Y Yellow
- T Transparent Blue

Flexcoil® Coiled Polyurethane with Reusable Fittings

Part Number, Fitting & Color Code	Fitting Options	Standard Colors	Material Length	Working Length	Retracted Length	OD	ID	Coil OD	Working Pressure	Weight
PR532-10			10'	8'	7"					.29 lbs.
PR532-15			15'	12.5'	9 1/2"					.37 lbs.
PR532-20	B= (2) 1/4" Swivel	B G R Y T	20'	17'	12 1/2"	1/4"	.160"	1 1/2"	150 PSI	.46 lbs.
PR532-25			25'	20'	15 1/2"					.54 lbs.
PR532-30			30'	25.5'	19"					.62 lbs.
PR316-5			5'	4'	2"					.23 lbs.
PR316-10			10'	8'	6"					.34 lbs.
PR316-15	B= (2) 1/4" Swivel	B G R Y T	15'	12.5'	10 1/4"	5/16"	3/16"	1 7/8"	160 PSI	.46 lbs.
PR316-20			20'	17'	14 1/2"					.56 lbs.
PR316-25			25'	20'	18 1/2"					.68 lbs.
PR14-5			5'	4'	2 1/2"					.26 lbs.
PR14-10			10'	8'	6"					.41 lbs.
PR14-15	—= (2) 1/4" Rigid		15'	12.5'	9 1/2"					.59 lbs.
PR14-20	A= (1) 1/4" Rigid	B G R Y T	20'	17'	13"	3/8"	1/4"	2 1/2"	130 PSI	.74 lbs.
PR14-25	(1) 1/4" Swivel		25'	20'	16"					.88 lbs.
PR14-30	B= (2) 1/4" Swivel		30'	25.5'	19"					1.05 lbs.
PR14-50			50'	42.5'	32 1/2"					1.50 lbs.
PR516-10			10'	8'	7 1/2"					.68 lbs.
PR516-15	4B= (2) 1/4" Swivel	B G R Y T	15'	12.5'	11 1/2"					.89 lbs.
PR516-20	B= (2) 3/8" Swivel		20'	17'	15"	15/32"	5/16"	2 15/16"	130 PSI	1.11 lbs.
PR516-25			25'	20'	19"					1.32 lbs.
PR516-30			30'	25.5'	23"					1.52 lbs.
PR38-10	4= (2) 1/4" Rigid		10'	8'	5 1/2"					1.00 lbs.
PR38-15	4A= (1) 1/4" Rigid		15'	12.5'	8 1/2"					1.40 lbs.
PR38-20	(1) 1/4" Swivel		20'	17'	11"					1.85 lbs.
PR38-25	4B= (2) 1/4" Swivel	B G R Y T	25'	20'	14"	9/16"	3/8"	4 1/8"	135 PSI	2.25 lbs.
PR38-30	—= (2) 3/8" Rigid		30'	25.5'	17"					2.63 lbs.
PR38-50	A= (1) 3/8" Rigid		50'	42.5'	27 1/2"					3.23 lbs.
	(1) 3/8" Swivel									
	B= (2) 3/8" Swivel									
PR12-10			10'	8'	7"					2.14 lbs.
PR12-15			15'	12.5'	11 3/4"					2.95 lbs.
PR12-20			20'	17'	16 1/2"					3.77 lbs.
PR12-25	B= (2) 1/2" Swivel	B G R Y T	25'	20'	23"	3/4"	.467"	4.5"	155 PSI	4.60 lbs.
PR12-30			30'	25.5'	28"					5.35 lbs.
PR12-50			50'	42.5'	40"					7.75 lbs.

Colors • Printing • Packaging

* In addition to color choice, select fittings for both ends of the coil.

USA & International: 503-434-5561

US Toll Free: 888-373-9233

31