

Thermostats & Hygrostats ***for temperature and humidity control***

- ***Superior Quality***
- ***Global listings***
- ***Excellent Value***
- ***In Stock***

Tamper-proof thermostats

- For **Cooling** (blue):
 - normally open contact, closes as temperature rises
 - Available pre-sets:
 - 95 °F / 35 °C
 - 122 °F / 50 °C
 - 140 °F / 60 °C



- For **Heating** (red):
 - normally closed contact, opens as temperature rises
 - Available pre-sets:
 - 41 °F / 5 °C
 - 59 °F / 15 °C



Adjustable thermostats

- Available for **Cooling** & **Heating**
- Thermostat available with remote capillary sensor
- Available with °F or °C scale

Adjustable hygrostat

- To maintain a set humidity level and avoid condensation



Adjustable hygrotherm

- To maintain temperature and humidity settings and protect the equipment



häwa thermostats, hygrostats and related equipment

DON'T FIND WHAT YOU NEED?

PLEASE ALSO CHECK OUR COMPLETE CATALOG

OR CALL US AT 1-800-783-4239

Tamper-proof thermostats

For regulation of cooling or heating equipment to maintain a desirable temperature inside an enclosure or cabinet for maximization of performance and life expectancy of the electric and electronic components.

Description	Switch on temperature	Switch off temperature	Order No.
NO contact – for cooling equipment	95 °F / 35 °C	77 °F / 25 °C	3150-4035-00-00
NO contact – for cooling equipment	122 °F / 50 °C	104 °F / 40 °C	3150-4050-00-00
NO contact – for cooling equipment	140 °F / 60 °C	122 °F / 50 °C	3150-4060-00-00
NC contact – for heating equipment	41 °F / 5 °C	59 °F / 15 °C	3150-3015-00-00
NC contact – for heating equipment	59 °F / 15 °C	77 °F / 25 °C	3150-3025-00-00

"NO" = normally open contact: contact closes once preset temperature is exceeded / "NC" = normally closed contact: contact opens once preset temperature is exceeded

Adjustable thermostats

For regulation of cooling or heating equipment to maintain a desirable temperature inside an enclosure or cabinet for maximization of performance and life expectancy of the electric and electronic components.

Application	Display dial in	Temperature range	Order No.
NO contact – for cooling equipment	°F	32 – 140 °F	3150-2060-02-27
NO contact – for cooling equipment	°C	0 – 60 °C	3150-2060-02-30
NC contact – for heating equipment	°F	32 – 140 °F	3150-1060-02-27
NC contact – for heating equipment	°C	0 – 60 °C	3150-1060-02-30

Capillary thermostat

Sensor on 5 ft capillary tube for inaccessible areas

Same as adjustable thermostats, but can be used for cooling **and** heating equipment.

Application	Display dial in	Temperature range	Order No.
For cooling & heating equipment	°C	0 – 60 °C	3150-0061-02-30

Adjustable hygrostat

A heater is turned on – temperature-independent – if the preset relative humidity is exceeded.

Application	Display dial in	Rel. humidity range	Order No.
For heating equipment	% rH	40 – 90 % rH	3150-0030-02-30

Electronic hygrotherm

A combination of thermostat and hygrometer to protect the components inside the enclosure.

Application	Display dial in	Ranges	Order No.
For cooling & heating equipment	°C / % rH	0 – 60 °C / 50 – 90 % rH	3150-0060-02-23

Electronic relay

Designed to switch high powered DC operated equipment up to 16 Amps.

Application	Nom. Voltage	Max. capacity	Order No.
All thermostats and hygrometers	24 V _{DC}	16 A @ 28 V _{DC}	3150-0010-00-24

