**P52 Stainless Steel Regulator** and Filter/Regulator



## **Features**

- Low Droop
- Tapped Vent
- Excellent Stability
- Port Sizes from 1/4" up to 1"

## **Applications**

- Sour Gas
- Corrosive Environments
- · Off Shore

The P52SS regulator is designed for service with a wide variety of corrosive gases and severe environments. It is the ideal choice for sour gas applications and where a corrosive environment is present.

The standard version of this regulator is relieving with no constant bleed. You must specify if a non-relieving regulator is required.

Key components to the filter / regulator include a built in dripwell, 25 micron stainless filter. Both the regulator and filter / regulator come standard with Viton elastomers and a 'T' handle adjustment.

## **P52SS Part Matrix**

<b>A</b>	<b>A</b>	<b>A</b>	<b>A</b>	Style
RX				Regulator
FR				Filter Regulator with Manual Drain
AR				Filter Reg with Auto Drain
				Body Size
	02			1/4 NPT
	03			3/8 NPT
	04			1/2 NPT
	06			3/4 NPT
	80			1 NPT
- "	_			Output Ranges
		030		3 - 30 PSIG
		060		6 - 60 PSIG
		125		12 - 125 PSIG
		150		15 - 150 PSIG
				Options
			00	Standard
			0B	Non-relieving
			OF	5 Micron Filter
			BF	Non-relieving & 5 Micron Filter
			OH BH	
			FH	Non-relieving Hex Head Adjustment 5 Micron Filter and Hex Head
				Non-relieving Hex Head
			СС	and 5 Micron Filter



opcomoduons	
Maximum Inlet Pressure	425 PSIG
	3 - 30 PSIG
Outlet Denge	6 - 60 PSIG
Outlet Ranges	12 - 125 PSIG
	15 - 150 PSIG
Repeatability	± 0.25 PSIG
	1/4" - 38 SCFM
Flow Rates	3/8" - 42 SCFM
at 100 PSIG Inlet	1/2" - 95 SCFM
20 PSIG Outlet	3/4" - 105 SCFM
	1" - 105 SCFM
Temperature Range	-4 to 176°F
Exhaust Capacity	0.1 SCFM
Max Air Consumption	0.5 SCFH
Filter	25 Micron
Supply Pressure Sensitivity at 25 PSIG	± 1.0 PSIG Change in Output
,	316 SS Housing
Material	Body and Filter,
	Viton Elastomers

## **Mounting Bracket**

607-309-000



