

FIELDBUS CONNECTORS

| Connection accessories | | | Art-No. |
|---|---|---|--------------------|
|  | T-coupler M12/M12, female/male straight, A-coded, 6-pole, shielded | Cube67 additional actuator power supply | 7000-46101-0000000 |
| | straight, A-coded, 4-pole | MASI68 additional actuator power supply | 7060-42701-0000000 |
|  | Male M12, field-wireable, screw terminals straight, B-coded, 5-pole, shielded | PROFIBUS, Interbus Cable diameter (6...8 mm) | 7000-14001-0000000 |
|  | Female M12, field-wireable, screw terminals straight, B-coded, 5-pole, shielded | PROFIBUS, Interbus Cable diameter (6...8 mm) | 7000-14021-0000000 |
|  | Male M12, field-wireable, screw terminals 90°, B-coded, 5-pole, shielded | PROFIBUS, Interbus Cable diameter (6...8 mm) | 7000-14011-0000000 |
| | 90°, D-coded, 4-pole, shielded | Ethernet CAT 5 Cable diameter (6...8 mm) | 7000-14581-0000000 |
|  | Female M12, field-wireable, screw terminals 90°, B-coded, 5-pole, shielded | PROFIBUS, Interbus Cable diameter (6...8 mm) | 7000-14031-0000000 |
|  | Male M12, field-wireable, IDC terminals straight, B-coded, 3-pole, shielded | PROFIBUS Cable diameter (7...8.8 mm) | 7000-14201-0000000 |
| | straight, D-coded, 4-pole, shielded | Ethernet CAT 5 Cable diameter (5.5...7.2 mm) | 7000-14521-0000000 |
|  | Female M12, field-wireable, IDC terminals straight, B-coded, 3-pole, shielded | PROFIBUS Cable diameter (7...8.8 mm) | 7000-14221-0000000 |
| | straight, D-coded, 4-pole, shielded | Ethernet CAT 5 Cable diameter (5.5...7.2 mm) | 7000-14621-0000000 |
|  | Male M12, field-wireable, screw terminals straight, A-coded, 5-pole | DeviceNet, CANopen Cable diameter (6...8 mm) | 7000-12761-0000000 |