

T-COUPLERS M8, M12, 7/8"

Connection cables

- M12 - M12

T-coupler (Slimline)

Male straight to female straight



Approvals: PCB UL US Listed

T-couplers M8, M12, 7/8"

| 1 Form | 41131 | 41151 | 41191 | 41135 |
|---|---|--------|--------|-------------------------------------|
| Type | 5-pole | 5-pole | 5-pole | 5-pole with 3 × LED (PNP) |
| Circuit diagram | | | | |
| Contact layout | | | | |
| Holding plate | 7000-99061-0000000 | | | |
| Holding plate and mounting set | 7000-99062-0000000 | | | |
| Technical Data | | | | |
| Operating voltage | max. 60 V AC/DC | | | 24 V DC ±25 % |
| Operating current per contact | max. 4 A | | | |
| Locking of ports | Screw thread M12 × 1 mm (recommended torque 0.6 Nm) self-securing | | | |
| Protection | IP65 and IP67 when plugged and screwed down (EN 60529) | | | |
| Temperature range | -25...+85 °C | | | |
| Article No. | | | | |
| The composition of your article number is explained on page 3.1.i | <u>7</u> <u>0</u> <u>0</u> <u>0</u> | - | - | <u>0</u> <u>0</u> <u>0</u> <u>0</u> |
| | 1 Form | | | |
| Notes | Other versions on request. | | | |