

PLUG CONNECTORS FOR FOOD & BEVERAGE

Open ended wires

– Valve Connectors

– Screw, Stainless Steel 1.4404 (V4A)

Form B (10 mm)



Form BI (11 mm)

Industrial standard



Approvals: SA^{US} ECOLAB

1 Form	10021	11021
Type	24 V AC/DC LED and suppression	24 V AC/DC LED and suppression
Circuit diagram		
Contact layout		
2 Cable Type	Jacket Color	Jacket Color
Wire diameter 0.75 mm ² PVC	gray 216	gray 216
3 Cable Length		
1.5 m	0150	
3.0 m	0300	
5.0 m	0500	
7.5 m	0750	
10.0 m	1000	
Technical Data		
Operating voltage	24 V AC/DC ±25 %	
Protection	IP65, IP68, IP69K when plugged and screwed down (EN 60529)	
Temperature range	-25...+85 °C	
Article No.		
The composition of your article number is explained on page 3.1.i	<div style="display: flex; justify-content: space-around; align-items: center;"> <u>7</u> <u>0</u> <u>1</u> <u>4</u> – – – </div>	
	1 Form	2 Cable Type
		3 Cable Length
Notes	Other versions on request. Further cable lengths on request.	

Plug Connectors for Food & Beverage