PLUG CONNECTORS FOR FOOD & BEVERAGE

Open ended wires

– Valve Connectors

– Screw, Stainless Steel 1.4404 (V4A)

Approvals: c SP us ECOLAB

	Form C (8 mm)	**Form CI (9.4 mm)** Industrial standard
1 Form	**80021**	**94021**
Type	**24 V AC/DC**	**24 V AC/DC**
	LED and suppression	**LED and suppression**
Circuit diagram		
Contact layout		
2 Cable Type	**Jacket Color**	**Jacket Color**
Wire diameter 0.75 mm²	**gray**	**gray**
PVC	**216**	**216**
3 Cable Length		
1.5 m	**0150**	
3.0 m	**0300**	
5.0 m	**0500**	
7.5 m	**0750**	
10.0 m	**1000**	
Technical Data		
Operating voltage	24 V AC/DC ±25 %	
Protection	IP65, IP68, IP69K when plugged and screwed down (EN 60529)	
Temperature range	-25...+85 °C	
Article No.		
The composition of your article number is explained on page 3.1.i	**7 0 1 4 – _ _ _ _ _ – _ _ _ _ _ _ _ _**	
	1 Form	**2 Cable Type** / **3 Cable Length**
Notes		
	Other versions on request. Further cable lengths on request.	

www.comoso.com