


VALVE CONNECTORS

SVS Eco

- Field-wireable
- Screw terminals
- without components

Approvals: 





Form A (18 mm)



Form A (18 mm)

for pressure switches



1 Form	29245	29405
Type	0...230 V AC/DC without components metric	0...230 V AC/DC without components metric
Circuit diagram		
Contact figure	Cable outlet can be turned in 90° steps	
Contact layout		
Technical Data		
Operating voltage	0...230 V AC/DC	
Operating current per contact	max. 10 A	
Connection cross section	0.5...1.5 mm ²	
Sealing range (cable diameter)	6...8 mm	
Locking of ports	M3 (recommended torque 0.4 Nm)	
Contact figure	Cable outlet can be turned in 90° steps	
Compression gland	M16 × 1.5 mm	
Protection	IP65 inserted and tightened	
Temperature range	-40...+80 °C	
Article No.		
The composition of your article number is explained on page 3.1.i	<div style="display: flex; justify-content: space-around; align-items: center;"> <u>7</u> <u>0</u> <u>0</u> <u>0</u> - _____ - <u>0</u> <u>0</u> <u>0</u> <u>0</u> <u>0</u> <u>0</u> <u>0</u> </div>	
	1 Form	
Notes	Other versions on request.	

Valve Connectors