

# VALVE CONNECTORS

SVS Eco

- Field-wireable
- Screw terminals
- without components

Approvals: 





Form A (18 mm)



Form A (18 mm)

for pressure switches




<b>1 Form</b>	<b>29245</b>	<b>29405</b>
Type	0...230 V AC/DC without components metric	0...230 V AC/DC without components metric
Circuit diagram		
Contact figure	Cable outlet can be turned in 90° steps	
Contact layout		
<b>Technical Data</b>		
Operating voltage	0...230 V AC/DC	
Operating current per contact	max. 10 A	
Connection cross section	0.5...1.5 mm <sup>2</sup>	
Sealing range (cable diameter)	6...8 mm	
Locking of ports	M3 (recommended torque 0.4 Nm)	
Contact figure	Cable outlet can be turned in 90° steps	
Compression gland	M16 × 1.5 mm	
Protection	IP65 inserted and tightened	
Temperature range	-40...+80 °C	
<b>Article No.</b>		
The composition of your article number is explained on page 3.1.i	<div style="display: flex; justify-content: space-around; align-items: center;"> <span><u>7</u> <u>0</u> <u>0</u> <u>0</u></span> <span>-</span> <span>_____</span> <span>-</span> <span><u>0</u> <u>0</u> <u>0</u></span> <span>  </span> <span><u>0</u> <u>0</u> <u>0</u> <u>0</u></span> </div>	
	<b>1 Form</b>	
Notes	Other versions on request.	

# VALVE CONNECTORS

SVS Eco

- Field-wireable
- Screw terminals
- without components

Approvals: 

Form B (10 mm)



Form BI (11 mm)






## 1 Form

29765

30005

Type	0...230 V AC/DC without components metric	0...230 V AC/DC without components metric
------	---	---

Circuit diagram		
-----------------	---	--

Contact figure	Cable outlet can be turned in 180° steps	
Contact layout		

## Technical Data

Operating voltage	0...230 V AC/DC	
Operating current per contact	max. 10 A	
Connection cross section	0.5...1.5 mm <sup>2</sup>	
Sealing range (cable diameter)	6...8 mm	
Locking of ports	M3 (recommended torque 0.4 Nm)	
Contact figure	Cable outlet can be turned in 180° steps	
Compression gland	M16 × 1.5 mm	M12 × 1.75 mm
Protection	IP65 inserted and tightened	
Temperature range	-40...+80 °C	

## Article No.

The composition of your article number is explained on page 3.1.i	<u>7</u> <u>0</u> <u>0</u> <u>0</u>	-	-	<u>0</u> <u>0</u> <u>0</u>	<u>0</u> <u>0</u> <u>0</u> <u>0</u>
---	-------------------------------------	---	---	----------------------------	-------------------------------------


1 Form

Notes	Other versions on request.
-------	----------------------------

# VALVE CONNECTORS

SVS Eco

- Field-wireable
- Screw terminals
- without components

Approvals: 




**Form C (8 mm)**



**Form CI (9.4 mm)**

Industrial standard



1 Form	30055	30155
Type	0...230 V AC/DC without components metric	0...110 V AC/DC without components metric
Circuit diagram		
Contact figure	Cable outlet can be turned in 90° steps	
Contact layout		
Technical Data		
Operating voltage	0...230 V AC/DC	0...110 V AC/DC
Operating current per contact	max. 6 A	
Connection cross section	0.34...0.5 mm <sup>2</sup>	
Sealing range (cable diameter)	4...6 mm	
Locking of ports	M2.5 (couple de serrage recommandé 0,4 Nm)	M3 (recommended torque 0.4 Nm)
Contact figure	Cable outlet can be turned in 90° steps	
Compression gland	M16 × 1.5 mm	M12 × 1.75 mm
Protection	IP65 inserted and tightened	
Temperature range	-40...+80 °C	
Article No.		
The composition of your article number is explained on page 3.1.i	<u>7 0 0 0</u> - <u>      </u> - <u>0 0 0</u>	<u>0 0 0 0</u>
	<b>1 Form</b>	
Notes	Other versions on request.	

Valve Connectors