

VALVE CONNECTORS

SVS Eco, LED

– Field-wireable

– Screw terminals

Form C (8 mm)



Approvals:

1 Form	30105	30115	30125
Type	24 V AC/DC	110 V AC/DC	230 V AC/DC
	LED and VDR metric	LED and VDR metric	LED and VDR metric
Circuit diagram			
Contact figure	Cable outlet can be turned in 90° steps		
Contact layout			
Technical Data			
Operating voltage	24 V AC/DC ±10 %	110 V AC/DC ±10 %	230 V AC/DC ±10 %
Operating current per contact	max. 1.5 A		
Connection cross section	0.34...0.5 mm ²		
Sealing range (cable diameter)	4...6 mm		
Locking of ports	M2.5 (couple de serrage recommandé 0,4 Nm)		
Compression gland	M12 × 1.75 mm		
Contact figure	Cable outlet can be turned in 90° steps		
Protection	IP65 inserted and tightened		
Temperature range	-40...+60 °C		
Article No.			
The composition of your article number is explained on page 3.1.i	<div style="display: flex; justify-content: space-around; align-items: center;"> <u>7 0 0 0</u> - _____ - <u>0 0 0</u> <u>0 0 0 0</u> </div>		
	1 Form		
Notes	Other versions on request.		

Valve Connectors