



Features

- Utilizes bellows mechanism to sense temperature
- High-quality snap-action switch
- Factory preset
- Shock and vibration resistant
- Available in a wide range of configurations
- NEMA 4, 13

Operating Specifications

Set Point Range	40° — 300°F	(4° — 149°C)
Set Point Tolerance	±5°F	(2.8°C)
Maximum Operating Temperature	100°F above set point (325°F max)	
Differential	8 — 16°F	
Current Rating	5 A @ 250 VAC	5 A @ 30 VDC (Resistive)
Media Connection	See Order Chart Below for Options	
Circuit Form	SPST-NO, SPST-NC or SPDT	
Electrical Connection	See Order Chart Below for Options	
Maximum External Pressure	500 PSI	

How to Order (Example: Part Number: **TM - 6A - 120R / WL**)

TM	-	6	-	A	-	1	2	0	R	/	WL	*
		Media Connection			Circuit Form	Fixed Set Point			Set Point Direction	Electrical Options		
1		1/2" NPT Male	A		SPST-NO	40°F — 300°F			R		WL	Wire Leads 18"
2		3/8" NPT Male	B		SPST-NC				F		QC	1/4" Spade Connection
6		M16 x 1.5	C		SPDT						WP	Weather Pack
7		1/2" BSPP Male (G1/2)									HR	DIN43650A Connector
											MP	Metri-Pack
											AT	10 A @ 125/250 VAC 5 A @ 30 VDC
											GG	Internal Ground
											AU	Gold Plate/Alloy for low currents

* Defaults to Screw Terminals