

**Hose Selector**
**Parker/Competitor Product Search**
**CrimpSource**
**Find a Distributor**
**Find a Specialty Distributor**
**How to Order**
**Air & Multipurpose**
**Chemical**
**Composite**
**Coolant & Engine**
**Dock**
**Equipment**
**Food & Beverage**
**Material Handling**
**Material Handling - Cergom**
**Oilfield**
**Petroleum**
**PVC**
**Silicone**
**Specialty**
**Steam**
**Water**
**Welding**
**Couplings / Accessories**

 Product Selector | **Series 7084** | Air and Multipurpose

**Twinhammer™ Dual Air/Water Jackhammer Hose Factory Assemblies**  
*- May be used as part of an OSHA-compliant silica dust suppression system*


Parker Series 7084 Twinhammer Hose is the first factory-assembled dual hose system that delivers both air and water in a single, unitized configuration for dust suppression in jackhammer/breaker tool applications, as required by new OSHA Respirable Crystalline Silica (RCS) requirements.

- The new twin line hose system concurrently:
- transfers air to power heavy duty pneumatic tools
  - transfers water to suppress silica dust produced by tool operation
  - helps create a safer and more efficient work environment

**Applications**

- Jackhammers, air compressors
- Wet method dust suppression hose system for pneumatic tools, including those subject to light oil mists for lubrication
- Construction, general industrial

Twinhammer hose assemblies feature durable, abrasion resistant and chemically bonded lines that provide easy handling while eliminating intrusive clamps, straps, tape or zip ties. The assemblies incorporate crimped-on universal end styles for quick connection/disconnection to the air system, and rust resistant crimped-on brass male NPT couplings for easy attachment to the water system.

To learn more about OSHA's Final Rule to Protect Workers from Exposure to Respirable Crystalline Silica, visit <http://www.osha.gov/silica/>.

<b>Tube:</b>	Black EPDM
<b>Reinforcement:</b>	Multiple textile plies
<b>Cover:</b>	<ul style="list-style-type: none"> <li>• 3/4 Air Hose: Red EPDM, smooth finish</li> <li>• 3/8 Water Hose: Blue EPDM, smooth finish</li> </ul>
<b>Temp Range:</b>	-40°F to +212°F (-40°C to +100°C)
<b>Brand Method:</b>	<ul style="list-style-type: none"> <li>• Air Hose: White ink</li> <li>• Water Hose: No brand</li> </ul>
<b>Brand Example:</b>	PARKER SERIES 7084 300 PSI MAX WP MADE IN USA (DATE CODE)
<b>Vacuum:</b>	Not recommended
<b>Industry Standards:</b>	Air Hose: ARPM Class C oil resistant tube
<b>Couplings:</b>	<ul style="list-style-type: none"> <li>• Air Hose: Crimped carbon steel universal couplings each end</li> <li>• Water Hose: Crimped brass 3/8 rigid male couplings each end</li> </ul>
<b>Packaging:</b>	Coiled and tied, no center disc; cartons

Part Number	IDs (in)	IDs (mm)	Reinf Plies	ODs (in)	ODs (mm)	Max Rec WP (psi)	Max Rec WP (bar)	Lengths (ft/m)	Approx. Wt (lbs/kg ea)	Std Pack Qty	Stock Status **
7084JHT75-600	3/4 3/8	19.1 9.5	2 2	1.2 0.7	29 17	300*	20.7	50 / 15	27 / 12	1	Y
7084JHT75-600B	3/4 3/8	19.1 9.5	2 2	1.2 0.7	29 17	300*	20.7	50 / 15	27 / 12	15	Y

**Table Notes**

\*\* **Stock:** "Y" indicates stocked item; "N" indicates non-stocked item. Stock status subject to change. Contact Parker Customer Service.

\* The air hose is rated to 300 psi maximum working pressure. The finished hose assembly is rated to 150 psi due to the limitation of the industry preferred fitting end style/connection.