

**Mini disposable inline desiccant dryer – DD10**

Used at the point-of-use, this disposable, mini inline desiccant dryer removes all traces of water vapor, oil vapor and dirt. It is often used directly upstream of blow guns or spray guns as final protection for critical parts blow off and paint spraying. Install in either direction; it functions in both directions.

A 40 micron, porous bronze element removes fine dirt particles, an oil removing media removes oil vapor, and desiccant beads absorb water vapor. The see-through housing shows desiccant color change from the original orange to a green color in the desiccant beads, which indicates that the dryer needs to be replaced.

**Features**

- Polycarbonate material allows clear desiccant visibility
- Disposable
- Used for parts blow off
- Protection for paint guns
- Non-toxic desiccant standard

**Specifications**

|   |                             |
|---|-----------------------------|
| <b>Housing</b> .....                      | Polycarbonate               |
| <b>Port threads</b> .....                 | 1/4" NPT                    |
| <b>Maximum flow capacity</b> .....        | 15 SCFM                     |
| <b>Maximum pressure rating</b> .....      | 125 PSIG (0 to 8,6 bar)     |
| <b>Maximum temperature rating</b> .....   | 130°F (54°C)                |
| <b>Operating temperature rating</b> ..... | 32°F to 130°F (0°C to 54°C) |
| <b>Weight</b> .....                       | 2.8 oz. (79.4 g)            |

**DD10-02****Installation**

The DD10 is equipped with a 1/4" NPT (F) and (M) ports and can be installed in either direction. When installing the filter/dryer hand tighten to a leak proof seal. Do not use any mechanical means to hold the filter/dryer and do not over torque the threads.

**Operation**

1. The unique feature of the filter/dryer design allows you to visually see when it is time to install a new DD10 by observing the color change from the original dark color to a complete light transparent color in the desiccant beads.
2. Do not attempt to clean the filter/dryer as the use of solvents, ketones, etc., will adversely affect the plastic housing.
3. Keep the hose free of snags. Extra tension on the filter/dryer assembly could break the unit at the connecting ports. To clear stuck hoses, grasp hose below the filter/dryer.

Non-metallic material is highly resistant to chemicals.

See through housing shows color change when dryer needs replacement.

