

# TRANSPORTATION 201, 206

## Performance



## 201

### Transportation

SAE 100R5 SAE J1402 AII / D.O.T. FMVSS 106 AII-AIR BRAKE



| #<br>Part Number | Hose I.D. |      | Hose O.D. |    | Working Pressure |      | Minimum Bend Radius |     | Weight |      | Vacuum Rating |     | Parkrimp  | Field Attachable |
|------------------|-----------|------|-----------|----|------------------|------|---------------------|-----|--------|------|---------------|-----|-----------|------------------|
|                  | inch      | mm   | inch      | mm | psi              | MPa  | inch                | mm  | lbs/ft | kg/m | of Hg         | kPa | 26 Series | 20/22 Series     |
| 201-4            | 3/16      | 5    | 0.52      | 13 | 3000             | 21   | 3                   | 75  | 0.15   | 0,22 | 28            | 95  | ●         | ●                |
| 201-5            | 1/4       | 6,3  | 0.58      | 15 | 3000             | 21   | 3-3/8               | 85  | 0.18   | 0,27 | 28            | 95  | ●         | ●                |
| 201-6            | 5/16      | 8    | 0.68      | 17 | 2250             | 15,7 | 4                   | 100 | 0.23   | 0,34 | 28            | 95  | ●         | ●                |
| 201-8            | 13/32     | 10   | 0.77      | 20 | 2000             | 14   | 4-1/2               | 115 | 0.27   | 0,40 | 28            | 95  | ●         | ●                |
| 201-10           | 1/2       | 12,5 | 0.92      | 23 | 1750             | 12,2 | 5-1/2               | 140 | 0.37   | 0,55 | 28            | 95  | ●         | ●                |
| 201-12           | 5/8       | 16   | 1.08      | 27 | 1500             | 10,5 | 6-1/2               | 165 | 0.40   | 0,60 | 28            | 95  | ●         | ●                |
| 201-16           | 7/8       | 22   | 1.23      | 31 | 800              | 5,6  | 7-3/8               | 185 | 0.46   | 0,68 | 20            | 68  | ●         | ●                |
| 201-20           | 1-1/8     | 29   | 1.50      | 38 | 625              | 4,3  | 9                   | 230 | 0.51   | 0,76 | 20            | 68  | ●         | ●                |
| 201-24           | 1-3/8     | 35   | 1.75      | 44 | 500              | 3,5  | 10-1/2              | 265 | 0.68   | 1,01 | 15            | 51  | ●         | ●                |
| 201-32           | 1-13/16   | 46   | 2.22      | 56 | 350              | 2,4  | 13-1/4              | 335 | 0.89   | 1,32 | 11            | 37  | ●         | ●                |
| 201-40           | 2-3/8     | 60   | 2.88      | 73 | 350              | 2,4  | 24                  | 610 | 1.31   | 1,95 | 11            | 37  | ●         | ●                |
| 201-48           | 3         | 76   | 3.56      | 90 | 200              | 1,4  | 33                  | 840 | 2.09   | 3,11 | 11            | 37  | ●         | ●                |

**Application:** Petroleum base hydraulic fluids and lubricating oils, diesel fuels and antifreeze solutions.

**Inner Tube:** Synthetic rubber.

**Reinforcement:** One fiber braid and one steel braid.

**Cover:** Fiber braid.

**Temperature Range:** -40°F to +302°F (-40°C to +150°C).

**Fittings:** 26 Series - pg. B-9.  
20 Series - pg. B-147.  
22 Series - pg. B-165.

- See page E-5 for charted effects temperature has on maximum working pressures of 201, 206, 213, and 266 hose.
- See Section B for Field Attachable Assembly Instructions.
- See Section C for Parkrimp Assembly Instructions.
- Temperature Range of other media listed in Section E.