

## 285

## Refrigerant

SAE J2064 TYPE C



# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		UHg Vacuum Rating		Parkrimp		Field Attachable	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs/ft	kg/m	inches of Hg	kPa	26 Series	21/23 Series		
285-4	3/16	5	0.49	11,7	500	3,4	1	25	0.09	0,14	28	95	•	•		
285-6	5/16	8	0.62	15,7	500	3,4	1-1/2	40	0.12	0,18	28	95	•	•		
285-8	13/32	10	0.74	18,8	500	3,4	2	50	0.17	0,25	28	95	•	•		
285-10	1/2	12,5	0.83	21,1	500	3,4	2-1/2	65	0.18	0,27	28	95	•	•		
285-12	5/8	16	0.96	24,4	500	3,4	3	75	0.23	0,34	28	95	•	•		

**Application:** Refrigerant 134a.**Inner Tube:** Synthetic rubber with nylon barrier.**Reinforcement:** One fiber braid.**Cover:** Synthetic rubber.**Temperature Range:** -22°F to +257°F (-30°C to +125°C).**Fittings:** 26 Series - pg. B-9.  
21 Series - pg. B-137.  
23 Series - pg. B-149.

## 244

## Refrigerant

SAE J2064 TYPE B, CLASS I



# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		UHg Vacuum Rating		Parkrimp	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs/ft	kg/m	inches of Hg	kPa	26 Series	
244-16	7/8	22	1.23	31	500	3,5	7-1/2	190	0.51	0,76	28	95	•	
244-20	1-1/8	29	1.50	38	500	3,5	9	230	0.56	0,83	28	95	•	
244-24	1-3/8	35	1.75	44	350	2,4	10-1/2	270	0.62	0,92	28	95	•	

**Application:** Refrigerant 134a.**Inner Tube:** Butyl rubber.**Reinforcement:** One braid steel wire.**Cover:** Fiber braid.**Temperature Range:** -22°F to +257°F (-30°C to +125°C).**Fittings:** 26 Series - pg. B-9.

- See Section B for Field Attachable Assembly Instructions.
- See Section C for Parkrimp Assembly Instructions.
- Temperature Range of other media listed in Section E.