



7122

LP Gas Vapor Hose

Series 7122

This product is designed for use as a light-duty, low pressure LP vapor transfer hose. It is recommended for applications such as space heaters used in chicken brooders and other farm and industrial applications.

Must be used in an outside or open environment.

4:1 Design factor

>> Economical; designed for light-duty service

Tube	Black Nitrile
Cover	Red Neoprene, pin pricked
Reinforcement	Multiple Textile Spirals
Temperature Range	-20°F to +160°F (-29°C to +71°C)
Branding	PARKER SERIES 7122 LPG VAPOR HOSE 125 PSI MAX WP MADE IN USA B2 (DATE CODE)
Brand Description	Ink Brand - Black letter color
Compare to	Gates LPG Vapor

LENGTHS: Reels are 650 ft. (+ 50 ft./-0 ft.) 90% 1 piece., 10% 2 pieces., 50 ft. min. length.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 7628. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

Part No.	ID (in.)	ID (mm)	Reinf. Spirals	OD (in)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7122-38200	3/8	9.5	2	0.656	16.7	14.9	3.8	125



WARNING! This hose should never exceed 125 PSI internal working pressure. This hose was designed for LP GAS - VAPOR ONLY type service. Not to be used for liquid LPG or barbecue grills – not UL listed. Should only be used in an outside, non-enclosed environment.

Applications

- Farm
- Industrial
- Heaters