

DAY-FLO® EPDM Heavy Duty Water Discharge Hose

Series 7306H

Series 7306H is a heavy duty discharge hose designed to handle alkalies, brine, glycols, herbicides, mild chemicals, slurries and water. The hose construction incorporates a heavy wall and elevated working pressure for durability and superior service. The EPDM cover is resistant to abrasion, heat, mild chemicals and weathering. Series 7306H is available in 200-foot continuous lengths.

Tube: Black EPDM Reinforcement: Multiple textile plies

Cover: Black EPDM; wrapped finish
Temp. Range: -30°F to +212°F (-34°C to +100°C)

Brand Method: White text on blue stripe

Brand Example: PARKER SERIES 7306H DAY-FLO H.D. WATER DISCHARGE HOSE XXX

PSI MAX WP MADE IN USA 001 (LOT#)

Design Factor: 4:1

Industry Standards: None applicable

Applications: • Alkalies, brine, glycols, herbicides, mild chemicals, slurries, water

· Agriculture, construction, general industrial, irrigation, surface mining

Vacuum: Not recommended

Compare to: Kuriyama Heavy Water Discharge; Veyance Plicord HD Water Discharge

Packaging: Coils

| Part Number | ID (in) | ID (mm) | Reinf Plies | OD (in) | OD (mm) | Approx Wt (lbs/ft) | Approx Wt (kg/ft) | Max Rec WP (psi) | Max Rec WP (bar) | Perm Cplg Rec | Std Pack Qty (ft) | Stock Status ** |
|----------------|------------|------------|----------------|------------|------------|--------------------------|-------------------------|------------------------|------------------------|---------------------|-------------------------|-----------------------|
| 7306H-1500 | 1-1/2 | 38.0 | 4 | 2.032 | 51.6 | 0.85 | 0.39 | 200 | 13.8 | * | 100 | N |
| 7306H-2000 | 2 | 50.8 | 4 | 2.536 | 64.4 | 1.10 | 0.50 | 200 | 13.8 | * | 100 | Υ |
| 7306H-2500 | 2-1/2 | 63.5 | 4 | 3.050 | 77.4 | 1.34 | 0.61 | 200 | 13.8 | * | 100 | Υ |
| 7306H-3000 | 3 | 76.2 | 4 | 3.550 | 90.1 | 1.59 | 0.72 | 200 | 13.8 | * | 100 | N |
| 7306H-4000 | 4 | 101.6 | 4 | 4.556 | 115.7 | 2.10 | 0.95 | 200 | 13.8 | * | 100 | Υ |
| 7306H-5000 | 5 | 127.0 | 4 | 5.582 | 141.7 | 2.75 | 1.25 | 200 | 13.8 | * | 100 | N |
| 7306H-6000 | 6 | 152.4 | 4 | 6.646 | 168.8 | 3.30 | 1.50 | 200 | 13.8 | * | 100 | Υ |
| 7306H-8000 | 8 | 203.2 | 4 | 8.644 | 219.6 | 4.35 | 1.97 | 200 | 13.8 | * | 100 | N |
| 7306H-10000 | 10 | 254.0 | 4 | 10.646 | 270.4 | 5.40 | 2.45 | 150 | 10.3 | * | 50 | Ν |

^{*} Couplings: Refer to CrimpSource at www.safehose.com for coupling recommendations and crimp specifications.

⚠ WARNING! Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.



^{**} Stock: "Y" indicates stocked item; "N" indicates non-stocked item. Stock status subject to change. Contact Parker Customer Service.