

MAXIFLEX® Lightweight Air Hose

Series 7308 and Series 7308E

Series 7308/7308E is a flexible, lightweight, medium pressure hose designed to handle air, mild chemicals and water. The rugged cover is resistant to abrasion and weathering. Series 7308/7308E provides service for low to medium pressure air and water applications in construction, general industrial, mines and quarries.

Tube: Black SBR

Reinforcement: Multiple textile plies

Cover: Yellow SBR; wrapped finish

Temp. Range: -20°F to +212°F (-29°C to +100°C)

Brand Method: Embossed

Brand Example: PARKER SERIES (7308) (7308E) MAXIFLEX AIR HOSE XXX PSI WP

Design Factor: 3:1

Industry Standards: None applicableApplications: • Air, water

Heavy duty air tools, compressors

Construction, general industrial, mines, quarries

Vacuum: Not recommended
Compare to: Veyance Plicord Air 300

Packaging: Coils

Series 7308

| Part Number | ID (in) | ID (mm) | Reinf Plies | OD (in) | OD (mm) | Approx Wt (lbs/ft) | Approx Wt (kg/ft) | Max Rec WP (psi) | Max Rec WP (bar) | Perm Cplg Rec | Std Pack Qty (ft) | Stock Status ** |
|----------------|------------|------------|----------------|------------|------------|--------------------------|-------------------------|------------------------|------------------------|---------------------|-------------------------|-----------------------|
| 7308-1004 | 1 | 25.4 | 2 | 1.488 | 37.8 | 0.49 | 0.23 | 250 | 17.2 | * | 100 | N |
| 7308-1254 | 1-1/4 | 31.8 | 2 | 1.772 | 45.0 | 0.63 | 0.32 | 250 | 17.2 | * | 100 | N |
| 7308-1504 | 1-1/2 | 38.1 | 2 | 2.031 | 51.6 | 0.74 | 0.43 | 250 | 17.2 | * | 100 | N |
| 7308-2004 | 2 | 50.8 | 4 | 2.598 | 66.0 | 1.08 | 0.61 | 250 | 17.2 | * | 100 | Υ |
| 7308-2504 | 2-1/2 | 63.5 | 4 | 3.051 | 77.5 | 1.20 | 0.74 | 250 | 17.2 | * | 100 | N |
| 7308-3004 | 3 | 76.2 | 4 | 3.528 | 89.6 | 1.35 | 0.88 | 250 | 17.2 | * | 100 | N |

^{*} Couplings: Refer to CrimpSource at www.safehose.com for coupling recommendations and crimp specifications.

Series 7308E

| Part Number | ID (in) | ID (mm) | Reinf Plies | OD (in) | OD (mm) | Approx Wt (lbs/ft) | Approx Wt (kg/ft) | Max Rec WP (psi) | Max Rec WP (bar) | Perm Cplg Rec * | Std Pack Qty (ft) | Stock Status ** | |
|----------------|------------|------------|----------------|------------|------------|--------------------------|-------------------------|------------------------|------------------------|--------------------------|-------------------------|-----------------------|--|
| 7308E-2000300 | 2 | 50.8 | 2 | 2.560 | 65.0 | 1.16 | 0.53 | 300 | 20.7 | * | 100 | Υ | |

^{*} Couplings: Refer to CrimpSource at www.safehose.com for coupling recommendations and crimp specifications.

⚠ WARNING! Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.



^{**} Stock: "Y" indicates stocked item; "N" indicates non-stocked item. Stock status subject to change. Contact Parker Customer Service.

^{**} Stock: "Y" indicates stocked item; "N" indicates non-stocked item. Stock status subject to change. Contact Parker Customer Service.