

56DH/568DH – Diagnostic Hose



Features

- Twin or multi-line available
- Compact OD, lightweight, flexible

Certifications

- MSHA Accepted for -2 only

Applications/Markets



- Hydraulic and pneumatic systems where a small O.D. hose is necessary
- Diagnostic equipment

Part Number		Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight		Permanent Fitting Series
#	#											
Natural	Non-Conductive	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
56DH-1.5	568DH-1.5	.09	2	.20	5	6,000	41.4	0.25	6	.02	.01	SF
56DH-2	568DH-2	.14	4	.32	8	6,000	41.4	0.50	13	.03	.05	CY

Construction

Tube: Nylon
 Reinforcement: Aramid fiber
 Cover: Polyurethane

Operating Parameters

Temperature Range:
 -40°F to +200°F (-40°C to +93°C)
 Change in working length @ Rated WPSI: ±2%
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

CY Series – pg. E-81
 SF Series – pg. E-85
 For Crimp Die Selection charts see pgs. G-30 : G-41
 Crimp information can be found online, for most Parker products, at www.parker.com/crimpsource

Colors

- Black
- Orange (Non-Conductive)

Notes

Perforated cover - 56DH
 Non-perforated cover - 568DH

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | parker.com/pfd

www.comoso.com

