

# 575X – Fast Response Hose



## Features

- Fast response even over longer lengths
- 5000 PSI constant pressure

## Certifications

- MSHA Accepted

## Applications/Markets



- Marine, offshore drilling
- Applications requiring fast and accurate response time

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
#												
	inch	mm	inch	mm	psi	MPa	inch	mm	inch	lbs./ft.	kg./mtr.	
575X-3	3/16	5	.43	11	5,000	34.5	1.50	38	28	.05	.07	55
575X-4	1/4	6	.51	13	5,000	34.5	2.00	51	28	.07	.10	55
575X-6	3/8	10	.64	16	5,000	34.5	3.00	76	28	.09	.13	55
575X-8	1/2	13	.81	21	5,000	34.5	4.00	102	28	.14	.21	55
575X-12	3/4	19	1.15	29	5,000	34.5	8.00	203	28	.24	.36	58H
575X-16	1	25	1.59	40	5,000	34.5	10.00	254	28	.36	.54	58H

## Construction

Tube: Nylon  
Reinforcement: Fiber  
Cover: Polyurethane

## Operating Parameters

Temperature Range:

-40°F to +212°F (-40°C to +100°C)

Change in working length @ Rated WPSI: ±2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

55 Series – pg. E-12

58H Series – pg. E-41

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

## Notes

Non-perforated cover

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)

[www.comoso.com](http://www.comoso.com)



A-47

Hose  
A

Tubing  
B

Coiled Air Hose  
& Fittings  
C

Transportation  
D

Fittings  
E

Tooling, Equipment  
& Accessories  
F

General Technical  
G