

# 1035HT – High Temperature Power Cleaning



## Features

- Non-marring
- Broad temperature range

## Applications/Markets



- Pressure washers (low pressure, high temperature)
- Carpet cleaning

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.	
#												
1035HT-3	3/16	5	.43	11	2,000	13.8	0.75	19	28	.04	.06	55
1035HT-4	1/4	6	.50	13	1,750	12.1	1.50	38	28	.06	.08	55
1035HT-6	3/8	10	.65	17	1,500	10.3	2.00	51	28	.09	.13	55

## Construction

Tube: Nylon  
 Reinforcement: Fiber  
 Cover: Polyurethane

## Operating Parameters

Temperature Range:  
 -40°F to +230°F (-40°C to +110°C)  
 Change in working length @ Rated WPSI: ±2%  
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

55 Series – pg. E-12  
 For Crimp Die Selection charts see pgs. G-30 : G-41  
 Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Yellow

## Notes

Perforated cover  
 No chlorinated solvents should be used  
 HBR (Hose Bend Restrictor) suggested for carpet cleaning applications - See Hose Guard in Tooling Equipment and Accessories Section pg. F-21

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)

[www.comoso.com](http://www.comoso.com)



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings  
 F Tooling, Equipment & Accessories  
 G General Technical