

CNG – Electrically Conductive Compressed Natural Gas Hose



Features

- Twin and multi-line available

Certifications

- Conforms to:
- NFPA 52
- ANSI/IAS NGV 4.2-1999
- CSA12.52-M99

Applications/Markets



- CNG Dispenser
- Fleet transit
- CNG Fuel transfer
- Residential CNG refueling

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Weight	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.
#										
5CNG-3	3/16	5	.43	11	5,000	34.5	1.50	38	.05	.07
5CNG-4	1/4	6	.62	16	5,000	34.5	2.00	51	.11	.16
5CNG-6	3/8	10	.65	16	5,000	34.5	3.00	76	.09	.13
5CNG-8	1/2	13	.90	23	5,000	34.5	4.00	102	.21	.31
5CNG-12	3/4	19	1.15	29	5,000	34.5	7.50	191	.24	.36
5CNG-16	1	25	1.59	40	5,000	34.5	10.00	254	.36	.53

Construction

Tube: Electrically conductive nylon
 Reinforcement: Fiber
 Cover: Polyurethane

Operating Parameters

Temperature Range:
 -40°F to +180°F (-40°C to +82°C)
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

Fittings

Factory-made assemblies only
 55 Series – pg. E-12 58 Series – pg. E-12
 58H Series – pg. E-41
 For Crimp Die Selection charts see pgs. G-30 : G-41

Colors

- Red

Notes

Perforated cover
 CNG hose must be assembled at the factory or by a Parflex approved facility
 Wire spring guards must be used on ANSI/CSA design certified CNG dispenser hose assembly sizes -3 through -8: single and multi-line bonded assemblies - pg. F-21

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | parker.com/pfd

www.comoso.com

