

SLH – Sewer Leader Hose



Features

- Easily identified black cover indicates termination of hose

Certifications

- NSWMA (National Solid Waste Management Association)
- WASTEC (Waste Equipment Technology Association)
- WEMI (Waste Equipment Management Institute)

Applications/Markets



- Leader hose for S4/S5/S6/S9 high-pressure sewer cleaning hose

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
#												
	inch	mm	inch	mm	psi	MPa	inch	mm	inch	lbs./ft.	kg./mtr.	
SLH-8	1/2	13	0.77	20	4,000	27.6	3.50	89	28	.25	.37	58/HY*
SLH-10	5/8	16	0.95	24	4,000	27.6	4.00	102	28	.38	.57	HY*
SLH-12	3/4	19	1.08	27	3,000	20.7	4.80	122	28	.45	.67	HY*
SLH-16	1	25	1.43	36	3,000	20.7	6.00	152	28	.80	1.19	HY*

Construction

Tube: Gray Copolyester

Reinforcement: Wire

Cover: Neoprene

Operating Parameters

Temperature Range:

-40°F to +150°F (-40°C to +66°C)

Min. Burst Pressure is 2.5x Max. Working Pressure at 73°F (23°C)

Fittings

58 Series – pg. E-12

HY Series – pg. E-87 (*HY Fittings available from Parker Hose Products Division)

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at www.parker.com/crimpsource

Colors

- Black

Notes

Not for use in hydraulic applications