



Presto Manifold

MATERIALS OF CONSTRUCTION	
MANIFOLD BODY:	GLASS FILLED NYLON
COLLET:	BRASS
O-RING:	BUNA N

NOMENCLATURE	
EXAMPLE: 24M-6-4	ATTRIBUTE:
24M	PRESTO MANIFOLD
6	INLET TUBE 6/16
4	OUTLET TUBE 4/16

SPECIFICATIONS	
PRESSURE RANGE:	UP TO 150 PSI
TEMPERATURE RANGES:	-40° TO +200°F

APPLICABLE TUBE	
TUBE MATERIAL:	NYLON, SAE J844 TYPE A & B NYLON TUBING
TUBE O.D.:	1/4, 3/8, 1/2



The Presto manifold provides a convenient junction to connect multiple tubing lines.

Assembly Instructions

1. Cut tubing squarely with Parker tube cutter PTC-001. Be certain that Manifold ports are clean and free of debris.
2. Insert tubing into port until it bottoms. Pull on tubing to verify that it is properly retained in the manifold.
3. To disassemble, simply hold release button against the manifold body and remove the tubing.
4. To reassemble, make certain that the Manifold ports are clean and free of debris and lubricate leading end of the tubing with light oil or petroleum jelly.

Presto Manifold 24M

PART NO.	TUBE O.D. INLET	TUBE O.D. OUTLET	A	B	D	G	H	M	M1	N
24M-4-4	1/4	1/4	1.33	3.98	.21	2.75	.53	.90	.88	.89
24M-6-4	3/8	1/4	1.33	4.00	.21	2.75	.53	.90	.88	.89
24M-6-6	3/8	3/8	1.65	6.49	.22	4.55	.60	1.02	1.02	1.33
24M-8-8	1/2	1/2	1.65	6.49	.22	4.55	.60	1.02	1.02	1.33
24M-8-6446	1/2	3/8 - 1/4	1.65	6.49	.22	4.55	.64	1.02	1.02	1.17

