



Parker Hannifin Corporation
Industrial Hose Division
30242 Lakeland Boulevard
Wickliffe, OH 44092-1747
Telephone: (440) 833-2120
Fax: (440) 833-2230
www.safehose.com

Sales Advisory



PRODUCT UPDATE

WILDCATTER® PROGRAM

Series 7216 Wildcatter Petroleum Transport Hose

*Update to Hose Brand/Layline, New Part Numbers and
Additional Crimp Specs (6" & 8" IDs Only)*



Series 7216 is a suction and discharge hose designed to handle oil and refined fuels such as biodiesel (to B20 in dedicated service), diesel, ethanol and gasoline as well as brine, mild chemicals, fracking fluids, drilling mud, petroleum waste, slurries and water. The hose construction incorporates a wire helix that provides full suction capability, kink resistance and a path to conduct a static electrical charge to ground. The cover is resistant to abrasion, oil and weathering.

New part numbers 7216-6002 and 7216-8002 are lighter weight and more flexible than the previous part numbers, and the 8" size now features a working pressure of 150 psi. The new part numbers supersede 7216-6004 and 7216-8004, which will be obsolete when current inventories are depleted.

NOTE:

- Refer to the table on pages 213-214 of Catalog 4800 for fuel compatibility and service conditions.

The Wildcatter trade name indicates the product is designed and manufactured for premium service in oilfield applications. However, Wildcatter products may be used in other industries, markets and applications where the product meets the required performance criteria.

(Continued on page 2)

If there are any questions please contact
Parker Customer Service toll-free at:

866.810.HOSE (4673)
Wickliffe, OH
Eastern USA

800.242.HOSE (4673)
South Gate, CA
Western USA





Parker Hannifin Corporation
Industrial Hose Division

Sales Advisory

Page 2

Series 7216 Wildcatter Petroleum Transport Hose *Update to Hose Brand/Layline, New Part Numbers and Additional Crimp Specs (6" & 8" IDs Only)*

Tube:	Black nitrile
Reinforcement:	Multiple textile plies with wire helix
Cover:	Black nitrile; wrapped finish
Temp Range:	-40°F to +200°F (-40°C to +93°C)
Brand Method:	Black text on orange stripe
Brand Example:	PARKER WILDCATTER 7216 TANK TRUCK HOSE 150 PSI MAX WP MADE IN USA
Design Factor:	4:1
Industry Standards:	None applicable
Applications:	<ul style="list-style-type: none"> • Biodiesel (to B20 in dedicated service), diesel, ethanol, gasoline, oil • Brine, crude oil, mild chemicals, petroleum waste, sediments, sludge, slurries, water • In-plant and storage tank transfer • Delivery, transport • General industrial, oilfield
Vacuum:	Full
Packaging:	Coils

Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.safehose.com.
Refer to the COS-K4 crimper for crimp specs for hose 4" ID and smaller. Refer to the COS-K6 or COS-K10 crimpers for hose IDs larger than 4".

Part Number	ID (in)	ID (mm)	Reinf Plies	OD (in)	OD (mm)	Approx Wt (lbs/ft)	Approx Wt (kgs/ft)	Min Bend Rad (in)	Min Bend Rad (mm)	Max Rec WP (psi)	Max Rec WP (bar)	Std Pack Qty (ft)	Stock Status **
NEW													
7216-6002	6	152.4	2	6.710	170.4	4.77	2.16	38.0	812.8	150	10.3	100	Y
7216-8002	8	203.2	2	8.750	222.3	6.95	3.15	52.0	1219.2	150	10.3	100	Y
PREVIOUS													
7216-6004	6	152.4	4	6.811	173.0	5.79	2.63	48.0	1219.2	150	10.3	100	n/a
7216-8004	8	203.2	4	8.976	228.0	9.42	4.27	72.0	1828.8	75	5.2	100	n/a

** Stock: "Y" indicates stocked item; "N" indicates non-stocked item. Stock status subject to change. Contact Parker Customer Service.

⚠ WARNING! Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.