



Parker Hannifin Corporation  
Industrial Hose Division  
30242 Lakeland Boulevard  
Wickliffe, OH 44092-1747

Telephone: (440) 833-2120  
Fax: (440) 833-2230  
www.safehose.com

## Sales Advisory



### PRODUCT UPDATE

### WILDCATTER® PROGRAM

### Series 7301 Wildcatter Hot Oilier Hose

### *Update to Hose Brand/Layline*



Series 7301 is a heavy duty, high pressure hose designed to circulate hot oil to clean out and increase flow in casings, piping, tanks and tubing. The hose construction incorporates multiple wire braids of reinforcement for crush resistance, durability, kink resistance and a path to conduct a static electrical charge to ground. The cover is resistant to abrasion, heat, oil and weathering.

#### NOTE:

- Refer to the table on pages 213-214 of Catalog 4800 for fuel compatibility and service conditions.

The Wildcatter trade name indicates the product is designed and manufactured for premium service in oilfield applications. However, Wildcatter products may be used in other industries, markets and applications where the product meets the required performance criteria.

*(Continued on page 2)*

If there are any questions please contact  
Parker Customer Service toll-free at:

866.810.HOSE (4673)  
Wickliffe, OH  
Eastern USA

800.242.HOSE (4673)  
South Gate, CA  
Western USA





Parker Hannifin Corporation  
Industrial Hose Division

## Sales Advisory

Page 2

### Series 7301 Wildcatter Hot Oiler Hose

#### Update to Hose Brand/Layline

<b>Tube:</b>	Black chloroprene
<b>Reinforcement:</b>	Multiple wire braids
<b>Cover:</b>	Black chloroprene; perforated wrapped finish
<b>Temp Range:</b>	-40°F to +275°F/300°F (-40°C to +135°C/149°C)
<b>Brand Method:</b>	Red text on black stripe
<b>Brand Example:</b>	PARKER <b>WILDCATTER</b> HOT OILER HOSE (ID) 2250 PSI MAX WP TEMP RATING 275°F CONTINUOUS 300°F INTERMITTENT
<b>Design Factor:</b>	3:1
<b>Industry Standards:</b>	None applicable
<b>Applications:</b>	<ul style="list-style-type: none"> <li>• Hot asphalt, glue, tar, oil, wax</li> <li>• In-plant transfer; delivery trucks</li> <li>• Construction, general industrial, oil field</li> </ul>
<b>Vacuum:</b>	Not recommended
<b>Packaging:</b>	Coils

#### Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at [www.safehose.com](http://www.safehose.com).  
Refer to the COS-K4 crimper for crimp specs for hose 4" ID and smaller. Refer to the COS-K6 or COS-K10 crimpers for hose IDs larger than 4".

Part Number	ID (in)	ID (mm)	Reinf Braids	OD (in)	OD (mm)	Approx Wt (lbs/ft)	Approx Wt (kgs/ft)	Min Bend Rad (in)	Min Bend Rad (mm)	Max Rec WP (psi)	Max Rec WP (bar)	Std Pack Qty (ft)	Stock Status **
7301-1502	1-1/2	38.1	2	2.000	50.8	1.59	0.72	13.0	330.2	2250	155.2	50	Y
7301-1502075	1-1/2	38.1	2	2.000	50.8	1.59	0.72	13.0	330.2	2250	155.2	75	Y

\*\* Stock: "Y" indicates stocked item; "N" indicates non-stocked item. Stock status subject to change. Contact Parker Customer Service.

**⚠ WARNING!** Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.