



Parker Hannifin Corporation
Industrial Hose Division
30242 Lakeland Boulevard
Wickliffe, OH 44092-1747

Telephone: (440) 833-2120
Fax: (440) 833-2230
www.safehose.com

Sales Advisory



PRODUCT UPDATE

WILDCATTER® PROGRAM

Series SS247 Wildcatter Material Handling Hose

Update to Hose Brand/Layline and Additional Crimp Specs



Series SS247 is a flexible, heavy duty discharge hose for dry abrasive materials—such as cement, pebble lime and sand—that are mixed to create wet cement and drilling mud. The static dissipating 1/4" SBR tube provides abrasion resistance and the SBR cover is resistant to abrasion, cuts, scuffs and weathering.

The Wildcatter trade name indicates the product is designed and manufactured for premium service in oilfield applications. However, Wildcatter products may be used in other industries, markets and applications where the product meets the required performance criteria.

(Continued on page 2)

If there are any questions please contact
Parker Customer Service toll-free at:

866.810.HOSE (4673)
Wickliffe, OH
Eastern USA

800.242.HOSE (4673)
South Gate, CA
Western USA



Parker Hannifin Corporation
Industrial Hose Division

Sales Advisory

Page 2

Series SS247 Wildcatter Material Handling Hose *Update to Hose Brand/Layline and Additional Crimp Specs*

Tube:	1/4" Black SBR; static dissipating
Reinforcement:	Multiple textile plies
Cover:	Black SBR; wrapped finish
Temp Range:	-40°F to +180°F (-40°C to +83°C)
Brand Method:	Black text on blue stripe
Brand Example:	PARKER WILDCATTER SS247 HEAVY DUTY DRY CEMENT XX PSI WP MADE IN USA
Design Factor:	3:1
Industry Standards:	None applicable
Applications:	<ul style="list-style-type: none"> • Dry abrasive materials, cement, pebble lime, powders, sand, silica • In-plant transfer/loading, bulk transport trucks • Construction, general industrial, oilfield
Vacuum:	Not recommended
Packaging:	Coils

Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.safehose.com.
Refer to the COS-K4 crimper for crimp specs for hose 4" ID and smaller. Refer to the COS-K6 or COS-K10 crimpers for hose IDs larger than 4".

Part Number	ID (in)	ID (mm)	Reinf Plies	OD (in)	OD (mm)	Approx Wt (lbs/ft)	Approx Wt (kgs/ft)	Max Rec WP (psi)	Max Rec WP (bar)	Std Pack Qty (ft)	Stock Status **
SS247-4000	4	101.6	2	4.75	120.7	2.49	1.13	75	5.2	100	Y
SS247-4500	4-1/2	114.3	2	5.25	133.4	2.79	1.27	75	5.2	-	N
SS247-5000	5	127.0	2	5.75	146.1	3.11	1.41	75	5.2	100	Y
SS247-6000	6	152.4	2	6.75	171.5	3.69	1.67	70	4.8	-	N
SS247-8000	8	203.2	2	8.75	222.3	4.88	2.21	60	4.1	-	N

** **Stock:** "Y" indicates stocked item; "N" indicates non-stocked item. Stock status subject to change. Contact Parker Customer Service.

⚠ WARNING! Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.