CHF- High Flow Series is a multistage vacuum generator. CHF unit is ideal for porous applications.

4 bolt mounting pattern with gauge opposite of vacuum and pressure inlet ports enables this generator to be panel mounted.

CHF Series comes standard with flow thru exhaust mufflers to reduce clogging in dirty environments. Additional Pneumatic Control Valve is required to create vacuum flow.



#### **Features**

- Classic multi-stage venturi
- Anodized aluminum body
- Aluminum body includes exhaust muffler
- Maximum vacuum level, 27.3 inHg
- Vacuum flow rates from 12.5 to 31.8 SCFM
- Mounting brackets included

## **Specifications**

Media	Non-lubricated air, non-corrosive gases						
Operating pressure	80 PSI						
Operating temperature	32°F to 120°F						
	Body: Aluminum						
Material	Nozzle & Diffuser: Polymer Seals: BUNA N						

# **CHF High Flow Vacuum Generators**

	Port size			Max. vacuum	Air	Max. degree of	Part number NPT	
	Pressure	Vacuum	Exhaust	flow SCFM	consumption SCFM	vacuum inHg		
Symbol	1/4	3/8	Muffler	20.9	6.5	27	CHF-20ZNE	
	1/4	3/8	Muffler	26.3	9.6	27	CHF-30ZNE	
V Optional MPS-34	1/4	3/8	Muffler	31.8	14.0	27	CHF-40ZNE	

**Vacuum Products** Vacuum Generators

MCA, CV,

#### **Accessories**

Port size	Description	Part number		
3/8	- Filter with 10 micron element	VFP2CFC01		
1/2	- Filter With 10 micron element	VFP3CFC01		
3/8	Filter with 10 micron element and	VFP2CFC03		
1/2	2 replacement elements	VFP3CFC03		

See Accessories Section for more options

## **VFP Series filter**



## Replacement components


Description	Part number
CHF- Repair kit	SFCHF90NN
0 to 30 inHg gauge	266298A
Bracket kit (Includes 4 brackets & 4 M5 x 15 screws	SFBW15
Silencer (flow thru)	SIS-001

Most popular.



## **Parker Pneumatic**

## **Dimensions**



Part number	Α	В	С	D	E	F	G	Н	J	K	L	М	N	Р	Q	Weight (grams)
CHF-20	7.64 (194)	3.15 (80)	1.89 (48)	2.72 (69)	1.97 (50)	1.81 (46)	4.84 (123)	1.69 (43)	.22 (5.5)	.94 (24)	.91 (23)	.51 (13)	6.26 (159)	1.26 (32)	.20 (5)	875
CHF-30	7.64 (194)	3.15 (80)	1.89 (48)	2.72 (69)	1.97 (50)	1.81 (46)	4.84 (123)	1.69 (43)	.22 (5.5)	.94 (24)	.91 (23)	.51 (13)	6.26 (159)	1.26 (32)	.20 (5)	885
CHF-40	7.64 (194)	3.15 (80)	1.89 (48)	2.72 (69)	1.97 (50)	1.81 (46)	4.84 (123)	2.28 (58)	.22 (5.5)	.94 (24)	.91 (23)	.51 (13)	6.26 (159)	1.26 (32)	.20 (5)	965

Inches (mm)

## SIS-001 silencer dimensions

