


**Features**

- Stainless steel or ceramic diaphragms
- UL listed and CE marked
- Sensor outputs
  - 2 PNP Open collector transistor Output, 30 VDC, 100mA
- Optional additional current, 4 to 20mA
- Output response time less than 5.0ms
- Polarity protected
- Short circuit protected
- 4 digit LED display
- Display head swivels 290°



**SCPSD-1000P-1727      SCPSD-600-14-15**


**SCPSD Ordering Numbers**

Pressure range	Port size	Electrical output	Electrical connection	Part number
-14.7 to 250 PSI	7/16-20 UNF-2b (SAE-4)	( 2 ) PNP	M12, 4 Pin	<b>SCPSD-0250P-0727</b>
-14.7 to 250 PSI	7/16-20 UNF-2b (SAE-4)	( 1 ) PNP with 4-20MA	M12, 4 Pin	<b>SCPSD-0250P-1727</b>
0 to 1000 PSI	7/16-20 UNF-2b (SAE-4)	( 2 ) PNP with 4-20MA	M12, 5 Pin	<b>SCPSD-1000P-1725</b>
0 to 1000 PSI	7/16-20 UNF-2b (SAE-4)	( 1 ) PNP with 4-20MA	M12, 4 Pin	<b>SCPSD-1000P-1727</b>
0 to 3000 PSI	7/16-20 UNF-2b (SAE-4)	( 2 ) PNP	M12, 4 Pin	<b>SCPSD-3000P-0727</b>
0 to 3000 PSI	7/16-20 UNF-2b (SAE-4)	( 1 ) PNP with 4-20MA	M12, 4 Pin	<b>SCPSD-3000P-1727</b>
0 to 3000 PSI	7/16-20 UNF-2b (SAE-4)	( 2 ) PNP with 4-20MA	M12, 5 Pin	<b>SCPSD-3000P-1725</b>
0 to 5000 PSI	7/16-20 UNF-2b (SAE-4)	( 1 ) PNP with 4-20MA	M12, 4 Pin	<b>SCPSD-5000P-1727</b>
0 to 5000 PSI	7/16-20 UNF-2b (SAE-4)	( 2 ) PNP with 4-20MA	M12, 5 Pin	<b>SCPSD-5000P-1725</b>
0 to 9000 PSI	7/16-20 UNF-2b (SAE-4)	( 2 ) PNP	M12, 4 Pin	<b>SCPSD-9000P-0727</b>
0 to 9000 PSI	7/16-20 UNF-2b (SAE-4)	( 2 ) PNP with 4-20MA	M12, 4 Pin	<b>SCPSD-9000P-1725</b>
-1 to 16 Bar	1/4 BSPP Male	( 2 ) PNP	M12, 4 Pin	<b>SCPSD-016-04-17</b>
-1 to 16 Bar	1/4 BSPP Male	( 2 ) PNP with 4-20ma	M12, 5 Pin	<b>SCPSD-016-14-15</b>
0 to 250 Bar	1/4 BSPP Male	( 2 ) PNP	M12, 4 Pin	<b>SCPSD-250-04-17</b>
0 to 250 Bar	1/4 BSPP Male	( 2 ) PNP with 4-20ma	M12, 5 Pin	<b>SCPSD-250-14-15</b>
0 to 600 Bar	1/4 BSPP Male	( 2 ) PNP	M12, 4 Pin	<b>SCPSD-600-04-17</b>
0 to 600 Bar	1/4 BSPP Male	( 2 ) PNP with 4-20ma	M12, 5 Pin	<b>SCPSD-600-14-15</b>

**Programming options**

Outputs change N.O. / N.C.	✓
Units of measure change	✓
Hysteresis mode	✓
Window comparator mode	✓
Auto teach mode	—
Output response time	✓
Lockout option	—
Password lockout	✓
Max. value display	—
Min. value display	—
Zero reset	✓
Red / Green LED display options	—
Error output mode	✓
Setting of decimal point	✓

**Dimensions**



Most popular.



C

Pressure Sensors  
 Vacuum Products

MPS-33  
 Series

MPS-34  
 Series

SCP01  
 Series

SCPSD  
 Series

Cables


**Specifications**

Pressure code	0250	016	1000	3000	5000	9000	250	600
Measure range PSI, (bar)	-14.7 to 250	(-1 to 16)	0 to 1000	0 to 3000	0 to 5000	0 to 9000	(0 to 250)	(0 to 600)
Overload pressure PSI, (bar)	725	(40)	2900	7250	11600	21750	(500)	(1200)
Burst pressure PSI, (bar)	725	(50)	11600	17400	24650	31900	(1200)	(2200)
Sensing element	Ceramic			Stainless steel				
Parts in contact with media	Stainless steel 1.4404			Stainless steel 1.4404, 1.4542, NBR*				
	Ceramic AL203, NBR*							
	*FPDM, EPDM special request							
Units of measure	PSI, bar, MPA							
Switch cycles	>100 million							
Output response time	< 10ms							
Power supply	15 to 30VDC, Class 2 power supply							
Short circuit protection	Yes, 2.4 amp / open collector output							
Reverse polarity protection	Yes							
Overload protection	Yes							
Current consumption	< 100mA							
Output circuit	2 PNP (Sourcing) open collector transistor							
Analog output	0/4...20mA, Programmable, freely scaleable							
Output functions	Hysteresis, Window comparator							
Switching voltage	-1.5VDC							
Maximum current output	1A with 2 open collector outputs, .5A per output							
Accuracy	± 0.5% F.S. Typ., ± 1% Max.							
Repeatability	± 0.25% F.S.							
Display accuracy	± 0.5% F.S. Typ., ± 1 Digit							
Thermal error max.	±0.03% F.S. at -4 to 185°F (-20 to 85°C)							
Material	Pressure Die-cast zinc Z 410: Surface-finishing							
Display material	Polyester							
General protection	IP 67, EN60529, UL, CE Marked, EMC-EN50082-2 Class B, EN 50081-2							
Temperature range of media	-4 to 185°F (-20 to 85°C)							
Ambient temperature range	-4 to 185°F (-20 to 85°C)							
Storage temperature	-40 to 212°F (-40 to 100°C)							
Display	4-Digit, 7-Segment LED, Red, 9mm height							
Tightening torque	35Nm							
Vibration resistance	20G, 10 to 500Hz, IEC60068-2-6							
Shock resistance	50 G, XYZ, 11ms, IEC60068-2-29							
Mass	10.6 oz. (300g)							


**C**  
**Pressure Sensors**  
**Vacuum Products**  
**MPS-33 Series**  
**MPS-34 Series**  
**SCP01 Series**  
**SCPSD Series**  
**Cables**

**Internal circuit**

**M12, 4-Pin, (2) PNP Outputs**



**M12, 5-Pin, (2) PNP Outputs with 4 to 20mA Analog**



**Note:** M12, 5-pin Female Cable Connector will fit on both M12, 4-pin and 5-pin Male Sensor Connector.

**M12, 4-Pin, (1) PNP Output with 4 to 20mA Analog**

