





aerospace  
climate control  
electromechanical  
filtration  
fluid & gas handling  
hydraulics  
**pneumatics**  
process control  
sealing & shielding



# Directional Control Valves

Series VA13 and VA15

3- and 5-port valves. G1/8

Catalogue PDE2617TCUK February 2016



ENGINEERING YOUR SUCCESS.

[www.comoso.com](http://www.comoso.com)

## Directional control valves

### Working medium, air quality

Working medium: Dry, filtered compressed air to  
ISO 8573-1 class 3.4.3.

### Recommended air quality

For best possible service life and trouble free operation, ISO 8573-1 quality class 3.4.3 should be used. This means 5µm filter (standard filter) dew point +3°C for indoor operation (a lower dew point should be selected for outdoor operation) and oil concentration 1.0 mg oil/m<sup>3</sup>, which is what a standard compressor with a standard filter gives.

### Compact installation dimensions - flexible installation



The VA13/15 valve range consists of spool valves of extremely robust design, incorporating a wide range of manual, mechanical and pilot-operated actuators.

### Rust and corrosion resistant designs.

The valve bodies and caps are made of brass. Stainless steel is used in the spools and the mechanical actuating devices. Versions intended for panel mounting have chromium-plated steel actuators and panel bezels.

### Mobile applications




The robust design, coupled with good corrosion resistance, makes the valves suitable for a wide range of applications. Manually operated valves are suitable for industrial and transport applications. The stable and ergonomically designed actuators make the valves easy to operate even with heavy working gloves.

### ISO 8573-1 quality classes

Quality class	Pollution		Water	Oil
	particle size (µm)	max. concentration (mg/m <sup>3</sup> )	max. press. dew point (°C)	max. concentration (mg/m <sup>3</sup> )
1	0,1	0,1	-70	0,01
2	1	1	-40	0,1
3	5	5	-20	1,0
4	15	8	+3	5,0
5	40	10	+7	25
6	-	-	+10	-

### High reliability



Valves easily comply with the requirements for component reliability in accordance with EU Machinery Directive standards EN292-2 and EN983.


The VA valves have few moving parts combined with short spool movement, these features combine to give valves having high reliability and long service life. The valves are designed for use with or without supplementary lubrication.

### Maintenance

When maintenance is required repair kits containing replacement seals are available. See page 15

**Directional control valves**

*Robust 3- and 5-port valves with brass bodies and stainless steel O-ring sealed spools.*



*Substantial actuating levers and knobs which can be operated by gloved hands.*

*Pneumatic, manual or mechanically actuated valves in a wide choice of types.*

*Suitable for panel mounting or direct mounting via integral mounting holes.*

*Most of the VA13 valves can be connected either as normally closed or normally open as required, by connecting the primary air supply to Port 1 or Port 3.*

**Ordering example****VA13-HIS4**

Valve type, VA \_\_\_\_\_  
 Valve size 1 = G1/8 \_\_\_\_\_  
 Number of ports, 3 or 5 \_\_\_\_\_  
 Type of actuation \_\_\_\_\_  
 Type of return \_\_\_\_\_  
 Type of installation \_\_\_\_\_  
 4 = panel mounted \_\_\_\_\_



Products specially suitable for the transport industry.


## Directional control valves

### Installation

Correctly mounted valves require only a minimum of maintenance. For maximum life, follow the instructions with regard to actuation directions, actuation speeds, angles and adjustments.

### Panel mounting

Mount the valves in a 40,5 mm diameter hole (thread M40 x 1,5). The panel-mounting collars have a flange on the front of the panel and a retaining nut behind the panel, for simple installation and clean and attractive appearance.




### Fitting adjustable roller actuators

The rest position of the actuating arm can be arranged at any required angle on the actuator shaft (360°).


The length of the arm is adjustable, and it can also be rotated through 180°. Note, however, that the roller must always be parallel to the valve body.

The arm can also be positioned on the other side of the valve by removing the actuating mechanism, turning it through 180° and reassembling it.




### Actuation

Maximum actuation distance (X), i.e. the maximum spool stroke length, is 4 mm. Valves are fully open after 3,5 mm travel. Type UW toggle cam actuators permit a vertical motion in toggle direction of up to 10 mm.



### Actuation speed as a function of actuation angle

Optimum valve life will be obtained if the shape of actuation cams is matched to the method of actuation employed. The principle is that the higher the speed of the actuating motion, the smaller the incident angle. The characteristic curve shown here plots the incident angle against speed of the actuating stroke.



### Actuation

Maximum actuation distance, the maximum spool stroke length is 7.6 mm.

### Actuation by adjustable roller

Actuation can be arranged in both directions if the arm is set as shown above. The arm needs to be moved through only 5° to make the valve change over, although a travel range of up to 90° can be accepted.

### Material specifications

Valve bodys, end covers,	Brass
spring guides	Polished stainless steel
Spools	Nitrile rubber
Seals	Zinc plated steel
Screws, nuts, washers	Steel
Balls	Acetal plastic
Push-buttons, knobs	Chrome-plated steel
Levers	Phosphatized cast-iron
Pedals	Hardened stainless steel
I-plunger	Acetal plastic
Rollers	















### IMPORTANT

Before servicing, make sure that the valve is depressurised. Disconnect the primary air hose to ensure that the air supply is safely interrupted before removing valves.



### Data

Working temperature:	-20 °C to +70 °C
Working pressure:	max 10 bar
Flow (acc. to ISO 6358)	
C:	0,9 NI/s, bar
Qn (P1=6 bar, Δp=1 bar):	3,6 l/s
Qmax:	6,3 l/s
Cv:	0,21

Symbol	Actuator	Return	Mounting	Changeover force at 6 bar	Weight kg	Order code
 	Push-button Red	Spring	Panel mounted	32,5 N	0,37	<b>VA13-HIS4</b>
	Push-button Black	Spring	Panel mounted	32,5 N	0,37	<b>VA13-HIS4A06*</b>
 	Push-button Red	Air signal	Panel mounted	6 N**	0,37	<b>VA13-HIA4</b>
 	Hand lever Held in two positions	Hand lever	Panel mounted	8 N	0,52	<b>VA13-HB24</b>
			Side mounted	8 N	0,35	<b>VA13-HB2</b>
 	Knob Red Two positions	Knob	Panel mounted	3 N	0,48	<b>VA13-KL24</b>
			Side mounted	3 N	0,31	<b>VA13-KL2</b>
 	Knob Red	Spring	Panel mounted	31,5 N	0,49	<b>VA13-KS4</b>
			Side mounted	31,5 N	0,32	<b>VA13-KS</b>
 	Knob Red Two positions	Knob/ Air signal	Panel mounted	6 N**	0,49	<b>VA13-KL2A4</b>
			Side mounted	6 N**	0,33	<b>VA13-KL2A</b>

\* Panel holder in black anodized aluminium.





















\*\* Without signal pressure. Signal pressure min 3 bar at 6 bar supply pressure.



All VA13 valves (except VA13-WGR and VA13-RWG) can be connected either as normally closed 3/2 valve (NC) or normally open 3/2 valve (NO) as required, by connecting the primary air supply to Port 1 or Port 3.

## Data

Working temperature:	-20 °C to +70 °C
Working pressure:	max 10 bar
Flow (acc. to ISO 6358)	
C:	0,9 Nl/s, bar
Qn (P1=6 bar, Δp=1 bar):	3,6 l/s
Qmax:	6,3 l/s
Cv:	0,21







	Symbol	Actuator	Return	Mounting	Changeover force at 6 bar	Weight kg	Order code
		Push-button Red	Spring	Panel mounted	34,5 N	0,46	<b>VA15-HIS4</b>
		Hand lever Held in two positions	Hand lever	Panel mounted	9 N	0,63	<b>VA15-HB24</b>
				Side mounted	9 N	0,45	<b>VA15-HB2</b>
		Hand lever Held in three positions	Hand lever	Panel mounted Closed centre position	9 N	0,63	<b>VA15-HB34</b>
		Hand lever Held in three positions	Hand lever	Panel mounted Exhausted centre position	9 N	0,63	<b>VA15-XHB34</b>
		Hand lever Three positions self-centring	Hand lever	Panel mounted Closed centre position	9 N	0,63	<b>VA15-HC4</b>
		Hand lever Three positions self-centring	Hand lever	Panel mounted Exhausted centre position	9 N	0,63	<b>VA15-XHC4</b>
		Knob Red Two positions	Knob	Panel mounted	5 N	0,58	<b>VA15-KL24</b>
				Side mounted	5 N	0,42	<b>VA15-KL2</b>
		Knob Red	Spring	Panel mounted	34,5 N	0,60	<b>VA15-KS4</b>
		Knob Red Two positions	Knob/Air signal	Panel mounted	8 N*	0,61	<b>VA15-KL2A4</b>

\*Without signal pressure. Signal pressure min 3 bar at 6 bar supply pressure.







**Data**

Working temperature:	-20 °C to +70 °C
Working pressure:	max 10 bar
Flow (acc. to ISO 6358)	
C:	0,9 NI/s, bar
Qn (P1=6 bar, Δp=1 bar):	3,6 l/s
Qmax:	6,3 l/s
Cv:	0,21

**VA13**

	Symbol	Actuator	Return	Mounting	Signal pressure min, bar at 6 bar actu./return	Weight Kg	Order code
		Air signal	Air signal	Side mounted	3/3	0,33	<b>VA13-AA</b>
		Air signal	Spring	Side mounted	4/-	0,32	<b>VA13-AS</b>
		Air signal with priority	Air signal	Side mounted	3/4	0,32	<b>VA13-ADA</b>

















**VA15**

	Symbol	Actuator	Return	Mounting	Signal pressure min, bar at 6 bar actu./return	Weight Kg	Order code
		Air signal	Air signal	Side mounted	3/3	0,33	<b>VA15-AA</b>
		Air signal	Spring	Side mounted	4/-	0,32	<b>VA15-AS</b>
		Air signal with priority	Air signal	Side mounted	3/4	0,32	<b>VA15-ADA</b>



## Data

Working temperature:	-20 °C to +70 °C
Working pressure:	max 10 bar max 8 bar for WGR and RWG
Flow (acc. to ISO 6358)	
C:	0,9 NI/s, bar
Qn (P1=6 bar, Δp=1 bar):	3,6 l/s
Qmax:	6,3 l/s
Cv:	0,21

	Symbol	Actuator	Return	Mounting	Changeover force at 6 bar	Weight kg	Order code
		Plunger	Spring	Side mounted	32,5 N	0,30	<b>VA13-IS</b>
		Plunger Two positions	Plunger	Side mounted	3 N	0,30	<b>VA13-II</b>
		Plunger	Air signal	Side mounted	6 N*	0,30	<b>VA13-IA</b>
		Roller one way trip	Spring	Side mounted	20,5 N	0,33	<b>VA13-UWS</b>
		Roller	Spring	Side mounted	32,5 N	0,33	<b>VA13-WS</b>
		Roller on an arm	Internal air min 4 bar	Side mounted Normally closed	0,6 N min	0,41	<b>VA13-WGR</b>
		Roller on an arm	Internal air min 4 bar	Side mounted Normally open	0,6 N min	0,41	<b>VA13-RWG</b>
		Roller	Spring	Side mounted		0,41	<b>VA13-LRS</b>

\* Without signal pressure. Signal pressure min 3 bar  
at 6 bar supply pressure.








All VA13 valves (except VA13-WGR and VA13-RWG) can be connected either as normally closed 3/2 valve (NC) or normally open 3/2 valve (NO) as required, by connecting the primary air supply to Port 1 or Port 3.




**Data**


Working temperature:	-20 °C to +70 °C
Working pressure:	max 10 bar max 8 bar for WGR
Flow (acc. to ISO 6358)	
C:	0,9 NI/s, bar
Qn (P1=6 bar, Δp=1 bar):	3,6 l/s
Qmax:	6,3 l/s
Cv:	0,21

	Symbol	Actuator	Return	Mounting	Changeover force at 6 bar	Weight kg	Order code
		Plunger	Spring	Side mounted	34,5 N	0,40	<b>VA15-IS</b>
		Plunger Two positions	Plunger	Side mounted	5 N	0,40	<b>VA15-II</b>
		Roller one way trip	Spring	Side mounted	21,6 N	0,43	<b>VA15-UWS</b>
		Roller	Spring	Side mounted	34,5 N	0,44	<b>VA15-WS</b>
		Roller on an arm	Internal air min 4 bar	Side mounted	0,6 N min	0,46	<b>VA15-WGR</b>
		Roller	Spring	Side mounted		0,46	<b>VA15-LRS</b>



## Dimensions




## Dimensions




## Dimensions



## Dimensions




## Dimensions




## Accessories

### Sintered bronze series




Port	Order code	Pack Qty
G1/8	9090050700	1

### Male straight connectors - Parallel thread



Tube Ø1	Thread B	Order code	Box Qty
4	1/8	F4PMB4-1/8	20
6	1/8	F4PMB6-1/8	30
8	1/8	F4PB8-1/8	40

## Service and Replacement Parts



### VA Series Heavy Duty Valves

Order code	Repair Kit
9128674100	Body seals (6 pcs. 'O' Ring)



#### Important !

Before carrying out any service work, ensure that the valve and manifold have been vented. Remove the primary supply air hose to ensure total disconnection of the air supply before dismantling valves or blank connection blocks.



#### NB !

All technical data in this catalogue is typical only.

The air quality is decisive for the valve life: see ISO 8573.



#### WARNING

FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS AND/OR SYSTEMS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.

This document and other information from Parker Hannifin Corporation, its subsidiaries and authorized distributors provide product and/or system options for further investigation by users having technical expertise. It is important that you analyze all aspects of your application and review the information concerning the product or system in the current product catalog. Due to the variety of operating conditions and applications for these products or systems, the user, through its own analysis and testing, is solely responsible for making the final selection of the products and systems and assuring that all performance, safety and warning requirements of the application are met. The products described herein, including without limitation, product features, specifications, designs, availability and pricing, are subject to change by Parker Hannifin Corporation and its subsidiaries at any time without notice.

#### SALE CONDITIONS

The items described in this document are available for sale by Parker Hannifin Corporation, its subsidiaries or its authorized distributors. Any sale contract entered into by Parker will be governed by the provisions stated in Parker's standard terms and conditions of sale (copy available upon request).



# Parker Worldwide

## Europe, Middle East, Africa

**AE – United Arab Emirates,**  
Dubai

Tel: +971 4 8127100  
parker.me@parker.com

**AT – Austria,** Wiener Neustadt

Tel: +43 (0)2622 23501-0  
parker.austria@parker.com

**AT – Eastern Europe,** Wiener  
Neustadt

Tel: +43 (0)2622 23501 900  
parker.easteurope@parker.com

**AZ – Azerbaijan,** Baku

Tel: +994 50 2233 458  
parker.azerbaijan@parker.com

**BE/LU – Belgium,** Nivelles

Tel: +32 (0)67 280 900  
parker.belgium@parker.com

**BG – Bulgaria,** Sofia

Tel: +359 2 980 1344  
parker.bulgaria@parker.com

**BY – Belarus,** Minsk

Tel: +375 17 209 9399  
parker.belarus@parker.com

**CH – Switzerland,** Etoy

Tel: +41 (0)21 821 87 00  
parker.switzerland@parker.com

**CZ – Czech Republic,** Klecany

Tel: +420 284 083 111  
parker.czechrepublic@parker.com

**DE – Germany,** Kaarst

Tel: +49 (0)2131 4016 0  
parker.germany@parker.com

**DK – Denmark,** Ballerup

Tel: +45 43 56 04 00  
parker.denmark@parker.com

**ES – Spain,** Madrid

Tel: +34 902 330 001  
parker.spain@parker.com

**FI – Finland,** Vantaa

Tel: +358 (0)20 753 2500  
parker.finland@parker.com

**FR – France,** Contamine s/Arve

Tel: +33 (0)4 50 25 80 25  
parker.france@parker.com

**GR – Greece,** Athens

Tel: +30 210 933 6450  
parker.greece@parker.com

**HU – Hungary,** Budaörs

Tel: +36 23 885 470  
parker.hungary@parker.com

**IE – Ireland,** Dublin

Tel: +353 (0)1 466 6370  
parker.ireland@parker.com

**IT – Italy,** Corsico (MI)

Tel: +39 02 45 19 21  
parker.italy@parker.com

**KZ – Kazakhstan,** Almaty

Tel: +7 7273 561 000  
parker.easteurope@parker.com

**NL – The Netherlands,** Oldenzaal

Tel: +31 (0)541 585 000  
parker.nl@parker.com

**NO – Norway,** Asker

Tel: +47 66 75 34 00  
parker.norway@parker.com

**PL – Poland,** Warsaw

Tel: +48 (0)22 573 24 00  
parker.poland@parker.com

**PT – Portugal,** Leca da Palmeira

Tel: +351 22 999 7360  
parker.portugal@parker.com

**RO – Romania,** Bucharest

Tel: +40 21 252 1382  
parker.romania@parker.com

**RU – Russia,** Moscow

Tel: +7 495 645-2156  
parker.russia@parker.com

**SE – Sweden,** Spånga

Tel: +46 (0)8 59 79 50 00  
parker.sweden@parker.com

**SL – Slovenia,** Novo Mesto

Tel: +386 7 337 6650  
parker.slovenia@parker.com

**TR – Turkey,** Istanbul

Tel: +90 216 4997081  
parker.turkey@parker.com

**UA – Ukraine,** Kiev

Tel: +380 44 494 2731  
parker.poland@parker.com

**UK – United Kingdom,** Warwick

Tel: +44 (0)1926 317 878  
parker.uk@parker.com

**ZA – South Africa,** Kempton Park

Tel: +27 (0)11 961 0700  
parker.southafrica@parker.com

## North America

**CA – Canada,** Milton, Ontario

Tel: +1 905 693 3000

**US – USA,** Cleveland

Tel: +1 216 896 3000

## Asia Pacific

**AU – Australia,** Castle Hill

Tel: +61 (0)2-9634 7777

**CN – China,** Shanghai

Tel: +86 21 2899 5000

**HK – Hong Kong**

Tel: +852 2428 8008

**IN – India,** Mumbai

Tel: +91 22 6513 7081-85

**JP – Japan,** Tokyo

Tel: +81 (0)3 6408 3901

**KR – South Korea,** Seoul

Tel: +82 2 559 0400

**MY – Malaysia,** Shah Alam

Tel: +60 3 7849 0800

**NZ – New Zealand,** Mt Wellington

Tel: +64 9 574 1744

**SG – Singapore**

Tel: +65 6887 6300

**TH – Thailand,** Bangkok

Tel: +662 186 7000

**TW – Taiwan,** Taipei

Tel: +886 2 2298 8987

## South America

**AR – Argentina,** Buenos Aires

Tel: +54 3327 44 4129

**BR – Brazil,** Sao Jose dos Campos

Tel: +55 12 4009 3500

**CL – Chile,** Santiago

Tel: +562 2303 9640

**MX – Mexico,** Toluca

Tel: +52 72 2275 4200

European Product Information Centre

Free phone: 00 800 27 27 5374

(from AT, BE, CH, CZ, DE, DK, EE, ES, FI,  
FR, IE, IL, IS, IT, LU, MT, NL, NO, PL, PT, RU,  
SE, SK, UK, ZA)

## Parker Hannifin Ltd.

Tachbrook Park Drive

Tachbrook Park, Warwick CV34 6TU

United Kingdom

Tel.: +44 (0) 1926 317 878

Fax: +44 (0) 1926 317 855

parker.uk@parker.com

www.parker.com

