SM382 HARVEST PLUS+ FOOD/BEVERAGE/WINE SUCTION

- Crush and kink resistant food hose suitable for milk, milk products, fruit juice, soft drinks, pharmaceutical products, and other non-oily liquid food products.
- Lightweight, easy to handle and bend due to its crush resistant monofilament helix reinforcement.
- Manufactured on stainless steel mandrels for an ultra-smooth bacteria free tube that will not impart taste or odor.
- EPDM cover assures excellent abrasion, ozone and mild chemical resistance.

Tube:Extruded white Chlorobutyl.Reinforcement:Textile with monofilament helix.Cover:Gray specially compounded EPDM.

Temperature: -40° to +225°F.

| | | | WORKING | WEIGHT | |
|--|--|-------------|--------------|--------|--------|
| I.D. | 0.D. | BEND RADIUS | PRESSURE PSI | LB/FT | VACUUM |
| 1 ¹ / ₂ " | 2 ¹ / ₄ " | 5" | 250 | 1.16 | Full |
| 2" | 2 ²⁵ /32" | 7" | 250 | 1.53 | Full |
| 2 ¹ / ₂ " | 39/32" | 13" | 250 | 1.93 | Full |
| 3" | 3 ²⁵ /32" | 21" | 250 | 2.27 | Full |
| 4" | 4 ²⁵ /32" | 40" | 200 | 3.03 | 15" |

Crush and kink resistant design.

Microbe and bacteria resistant tube.

Meets FDA, USDA, 3A and PMO sanitary requirements.



SP330 LIGHT-N-BRIGHT FOOD & BEVERAGE HOSE - CHLOROBUTYL TUBE

- Lightweight, ultra-flexible specialty hose designed for handling food, beverages, and other sanitary products.
- Outer PVC helix design allows the hose to glide easily across plant floors while providing excellent abrasion resistance.

Tube: Extruded white Chlorobutyl.

Reinforcement: Textile supported by an external PVC helix.

Cover: Red synthetic rubber. **Temperature:** -40° to +180°F.

| I.D. | 0.D. | BEND RADIUS | WORKING PRESSURE PSI | WEIGHT LB/FT | VACUUM |
|--|--|-------------|-------------------------|-----------------|--------|
| 2" | 3" | 2" | 150 | 1.39 | Full |
| 2 ¹ / ₂ " | 3 ¹ / ₂ " | 3" | 150 | 1.73 | Full |
| 3" | 4" | 4" | 150 | 2.48 | Full |
| 4" | 5" | 6" | 150 | 3.53 | Full |

SP100 slinky sleeves recommended for banding (Page 54).

Microbe and bacteria resistant tube.

Meets FDA, USDA, 3A, and PMO sanitary requirements.

