

Weatherhead Conversion Kit For use with 26, 43 and HY Series Fittings ONLY.

Now you can convert Weatherhead T-400 Crimpers to utilize Parker Parkrimp No-Skive thru-the-cover fittings. Crimping is easy and quick using Parkrimp 8WC-001 Conversion Kit.

Standard Equipment

| Model 8WC-001 for T-400 machines includes: | | | | |
|--|---------|--|--|--|
| Bowl Assembly | 8PC-030 | | | |
| Pusher | 8WC-00P | | | |
| Silver Die Ring | 81C-R01 | | | |
| Black Die Ring | 81C-R02 | | | |

Black Die Ring 43 Series Dies (Silver)

| 45 Series Dies (Silver) | | | |
|-------------------------|---------------------------|---------|--|
| • -4 (1/4") | Cavity Color Coded Red | 80C-A04 | |
| • -6 (3/8") | Cavity Color Coded Yellow | 80C-A06 | |
| • -8 (1/2") | Cavity Color Coded Blue | 80C-A08 | |
| • -12 (3/4") | Cavity Color Coded Green | 80C-A12 | |
| | | | |

Optional Tooling:

• -8 (1/2")

• -10 (5/8")

· -12 (3/4")

| Optional 10 | oning. | | | |
|------------------------------------|---------------------------|-----------|--|--|
| 43 Series Dies (Silver) | | | | |
| • -5 (5/16") | Cavity Color Coded Purple | 80C-A05 | | |
| • -10 (5/8") | Cavity Color Coded Orange | 80C-A10 | | |
| 26 Series Dies (Silver) | | | | |
| • -4 (3/16") | Cavity Color Coded Red | 80C-E04 | | |
| • -5 (1/4") | Cavity Color Coded Purple | 80C-E05 | | |
| -6 (5/16") | Cavity Color Coded Yellow | 80C-E06 | | |
| • -8 (13/32") | Cavity Color Coded Blue | 80C-E08 | | |
| -10 (1/2") | Cavity Color Coded Orange | 80C-E10 | | |
| -12 (5/8") | Cavity Color Coded Green | 80C-E12 | | |
| HY Series Dies - AX Hose (Silver) | | | | |
| • -4 (1/4") | Cavity Brown | 80C-H585 | | |
| • -6 (3/8") | Cavity Brown | 80C-H735 | | |
| • -8 (1/2") | Cavity Brown | 80C-H840 | | |
| • -10 (5/8") | Cavity Brown | 80C-H970 | | |
| -12 (3/4") | Cavity Brown | 80C-H1120 | | |
| HY Series Dies - BXX Hose (Silver) | | | | |
| • -4 (1/4") | Cavity Brown | 80C-H605 | | |
| • -6 (3/8") | Cavity Brown | 80C-H775 | | |

Cavity Brown

Cavity Brown

Cavity Brown

Note: For additional information and operating instructions, reference Hose Products Division Bulletin #4480-B10.

Note: For crimping information, see pages C-22—C-23.

Note: Hose assemblies must be inspected for cleanliness and free of all foreign particles.

Note: Parker Hannifin will not accept responsibility for the operation of, or provide warranty coverage for, a crimper that is operated by a power unit other than equipment supplied by Parker Hannifin for the express purpose of operating the crimper.



80C-H885

80C-H1010

80C-H1170